MAJOR TECHNICAL SPECIFICATIONS

Item / Area				U.S.A.			
Cab Type				Regular			
Vehicle Grade				Deluxe			
Model Code				GSK50L-TRADKA	GSK51L-THADKA	UCK50L-TRADKA	UCK51L-THADKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2
	Wheel Base		mm (in.)	3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	—	—	—	—
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	—	—	—	—
	Shoulder Room	Front	mm (in.)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)
		Rear	mm (in.)	—	—	—	—
	Cargo Space	Length	mm (in.)	2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	265 (10.4)	260 (10.2)	265 (10.4)	265 (10.4)
	Angle of Approach		degrees	27	28	27	27
	Angle of Departure		degrees	26	25	27, 22*3	26, 21*3
	Curb Weight*6	Front	kg (lb)	1198 (2640)	1236 (2725)	1254 (2765)	1297 (2860)
		Rear	kg (lb)	923 (2035)	934 (2060)	959 (2115)	966 (2130)
		Total	kg (lb)	2121 (4675)	2170 (4785)	2214 (4880)	2263 (4990)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	2810 (6200)	2900 (6400)	2990 (6600)	3080 (6800)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	180 (111)	180 (111)
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	180 (111)	180 (111)
	Acceleration	0 to 60 mph	sec.	8.4	8.6	7.4, 7.3*3	7.6, 7.5*3
		0 to 400 m	sec.	16.5	16.6	15.7	15.8
	Max. Permissible Speed	1st Gear	km/h (mph)	59 (36)	59 (36)	61 (37), 58 (36)*3	61 (37), 58 (36)*3
		2nd Gear	km/h (mph)	102 (63)	102 (63)	105 (65), 100 (62)*3	105 (65), 100 (62)*3
		3rd Gear	km/h (mph)	148 (91)	148 (91)	154 (95), 147 (91)*3	154 (95), 147 (91)*3
		4th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)	180 (111)
		5th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)	180 (111)
		6th Gear	km/h (mph)	—	—	—	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)
		Curb to Curb	m (ft.)	11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)
Engine	Engine Type			1GR-FE	1GR-FE	2UZ-FE	2UZ-FE
	No. of Cyls. & Arrangement			6-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			24-valve DOHC with VVT-i	24-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	3956 (241.4)	4664 (284.5)	4664 (284.5)
	Compression Ratio			10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			91 or higher	91 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	176/5200 (236/5200)	176/5200 (236/5200)	202/5400 (271/5400)	202/5400 (271/5400)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	361/4000 (266/4000)	361/4000 (266/4000)	424/3400 (313/3400)	424/3400 (313/3400)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output		Watts	1200	1200	1200, 1560*3	1200, 1560*3
	Starter Output		kW	1.6, 2.0*7	1.6, 2.0*7	1.4, 2.0*7	1.4, 2.0*7
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A750E (5A/T)	A750E (5A/T)	A750E (5A/T)	A750E (5A/T)
	Gear Ratio	In First		3.520	3.520	3.520	3.520
		In Second		2.042	2.042	2.042	2.042
		In Third		1.400	1.400	1.400	1.400
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.716	0.716	0.716	0.716
		In Sixth		—	—	—	—
		In Reverse		3.224	3.224	3.224	3.224
	Transfer Gear Ratio H4/L4			—	—	—	—
	Differential Gear Ratio (Front/Rear)			—/3.909	—/3.909	—/3.909, 4.100*3	—/3.909, 4.100*3
	Differential Gear Size (Front/Rear)		mm (in.)	—/241.3 (9.5)	—/241.3 (9.5)	—/241.3 (9.5)	—/241.3 (9.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18 : 1	18 : 1	18 : 1	18 : 1
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: P255/70R18
*2: P275/65R18 or P275/55R20
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification

U.S.A.					
Regular					
Deluxe					
UCK55L-TRADKA	UCK56L-THADKA	USK50L-TRTDKA	USK51L-THTDKA	USK55L-TRTDKA	USK56L-THTDKA
5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2
3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
—	—	—	—	—	—
1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
—	—	—	—	—	—
1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)
—	—	—	—	—	—
2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)
1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
275 (10.8)	275 (10.8)	265 (10.4)	265 (10.4)	275 (10.8)	270 (10.6)
28	28	27	27	28	28
27, 22*3	27, 21*3	27, 22*3	26, 21*3	27, 22*3	26, 21*3
1361 (3000)	1408 (3105)	1281 (2825)	1313 (2895)	1381 (3045)	1418 (3125)
975 (2150)	975 (2150)	966 (2130)	987 (2175)	991 (2185)	1002 (2210)
2336 (5150)	2384 (5255)	2248 (4955)	2300 (5070)	2372 (5230)	2420 (5335)
—	—	—	—	—	—
—	—	—	—	—	—
3080 (6800)	3175 (7000)	2990 (6600)	3175 (7000)	3080 (6800)	3265 (7200)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—	—	—	—
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
7.8, 7.7*3	7.9, 7.8*3	6.7, 6.4*3	6.8, 6.6*3	7.0, 6.7*3	7.1, 6.9*3
16.0, 15.9*3	16.1, 16.0*3	15.1, 14.9*3	15.2, 15.0*3	15.3, 15.2*3	15.5, 15.3*3
61 (37)*4, 58 (36) *3, 4, 23 (14)*5, 22 (13)*3, 5	61 (37)*4, 58 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38), 59 (36)*3	62 (38), 59 (36)*3	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
105 (65)*4, 100 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	105 (65)*4, 100 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65), 101 (62)*3	106 (65), 101 (62)*3	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95), 147 (91)*3	154 (95), 147 (91)*3	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
—	—	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)
11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)
2UZ-FE	2UZ-FE	3UR-FE	3UR-FE	3UR-FE	3UR-FE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
4664 (284.5)	4664 (284.5)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
10.0 : 1	10.0 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
202/5400 (271/5400)	202/5400 (271/5400)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
424/3400 (313/3400)	424/3400 (313/3400)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
1200, 1560*3	1200, 1560*3	1200, 1800*3	1200, 1800*3	1200, 1800*3	1200, 1800*3
1.4, 2.0*7	1.4, 2.0*7	2.0	2.0	2.0	2.0
—	—	—	—	—	—
A750F (5A/T)	A750F (5A/T)	AB60E (6A/T)	AB60E (6A/T)	AB60F (6A/T)	AB60F (6A/T)
3.520	3.520	3.333	3.333	3.333	3.333
2.042	2.042	1.960	1.960	1.960	1.960
1.400	1.400	1.353	1.353	1.353	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.716	0.716	0.728	0.728	0.728	0.728
—	—	0.588	0.588	0.588	0.588
3.224	3.224	3.061	3.061	3.061	3.061
1.000/2.618	1.000/2.618	—	—	1.000/2.618	1.000/2.618
3.909, 4.100*3/3.909, 4.100*3	3.909, 4.100*3/3.909, 4.100*3	—/4.100, 4.300*3	—/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3
220.0 (8.7)/241.3 (9.5)	220.0 (8.7)/241.3 (9.5)	—/266.7 (10.5)	—/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18 : 1	18 : 1	18 : 1	18 : 1	18 : 1	18 : 1
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item / Area				U.S.A.			
Cab Type				Regular		Double	
Vehicle Grade				Deluxe		SR5	
Model Code				USK55L-TRTDGA	USK56L-THTDGA	GSK51L-CRASKA	UCK51L-CRASKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5330 (209.8)	5810 (228.7)	5810 (228.7)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*1, 1925 (75.8)*2	1930 (76.0)*1, 1925 (75.8)*2
	Wheel Base		mm (in.)	3220 (126.8)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	—	—	982 (38.7)	982 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	—	—	882 (34.7)	882 (34.7)
	Shoulder Room	Front	mm (in.)	1694 (66.7)	1694 (66.7)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	—	—	1668 (65.7)	1668 (65.7)
	Cargo Space	Length	mm (in.)	2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	275 (10.8)	270 (10.6)	265 (10.4)	265 (10.4)
	Angle of Approach		degrees	28	28	28	28
	Angle of Departure		degrees	27, 22*3	25, 20*3	25	25, 20*3
	Curb Weight*6	Front	kg (lb)	1381 (3045)	1418 (3125)	1286 (2835)	1349 (2975)
		Rear	kg (lb)	991 (2185)	1002 (2210)	1000 (2205)	1025 (2260)
		Total	kg (lb)	2372 (5230)	2420 (5335)	2286 (5040)	2375 (5235)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3080 (6800)	3265 (7200)	2900 (6400)	3035 (6700)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)
	Max. Cruising Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)
	Acceleration	0 to 60 mph	sec.	7.0, 6.7*3	7.1, 6.9*3	9.0	7.9, 7.8*3
		0 to 400 m	sec.	15.3, 15.2*3	15.5, 15.3*3	16.9	16.0
	Max. Permissible Speed	1st Gear	km/h (mph)	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)	61 (37), 58 (36)*3
		2nd Gear	km/h (mph)	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	102 (63)	105 (65), 100 (62)*3
		3rd Gear	km/h (mph)	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	148 (91)	154 (95), 147 (91)*3
		4th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	180 (111)
		5th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	180 (111)
		6th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	12.88 (42.3)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
		Curb to Curb	m (ft.)	11.96 (39.2)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
Engine	Engine Type			3UR-FBE	3UR-FBE	1GR-FE	2UZ-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	24-valve DOHC with VVT-i	32-valve DOHC with VVT-i
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 84.0 (3.70 × 3.31)
	Displacement		cm^3 (cu.in.)	5663 (345.6)	5663 (345.6)	3956 (241.4)	4664 (284.5)
	Compression Ratio			10.2 : 1	10.2 : 1	10.0 : 1	10.0 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	91 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	284/5600 (381/5600)	284/5600 (381/5600)	176/5200 (236/5200)	202/5400 (271/5400)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	544/3600 (401/3600)	544/3600 (401/3600)	361/4000 (266/4000)	424/3400 (313/3400)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output		Watts	1200, 1800*3	1200, 1800*3	1200	1200, 1560*3
	Starter Output		kW	2.0	2.0	1.6, 2.0*7	1.4, 2.0*7
Chassis	Clutch Type			—	—	—	—
	Transmission Type			AB60F (6A/T)	AB60F (6A/T)	A750E (5A/T)	A750E (5A/T)
	Gear Ratio	In First		3.333	3.333	3.520	3.520
		In Second		1.960	1.960	2.042	2.042
		In Third		1.353	1.353	1.400	1.400
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.728	0.728	0.716	0.716
		In Sixth		0.588	0.588	—	—
		In Reverse		3.061	3.061	3.224	3.224
	Transfer Gear Ratio H4/L4			1.000/2.618	1.000/2.618	—	—
	Differential Gear Ratio (Front/Rear)			4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	—/3.909	—/3.909, 4.100*3
	Differential Gear Size (Front/Rear)		mm (in.)	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	—/241.3 (9.5)	—/241.3 (9.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18 : 1	18 : 1	18 : 1	18 : 1
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: P255/70R18
*2: P275/65R18 or P275/55R20
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification

	U.S.A.					
	Double					
	Limited	SR5		Limited	SR5	
	UCK51L-CRALKA	UCK52L-CHASKA	UCK56L-CRASKA	UCK56L-CRALKA	UCK57L-CHASKA	USK51L-CRTSKA
5	5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)	6290 (247.6)	5810 (228.7)
	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
	1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*1, 1925 (75.8)*2
	3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)	4180 (164.6)	3700 (145.7)
	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
15	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
	2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)	2480 (97.6)	2000 (78.7)
	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
20	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	260 (10.2)	260 (10.2)	275 (10.8)	270 (10.6)	270 (10.6)	265 (10.4)
	28	28	29	29	29	28
	25, 20*3	20	25, 20*3	25, 20*3	20	25, 20*3
25	1340 (2955)	1413 (3115)	1467 (3235)	1461 (3220)	1533 (3380)	1359 (2995)
	1039 (2290)	1032 (2275)	1046 (2305)	1052 (2320)	1048 (2310)	1043 (2300)
	2379 (5245)	2445 (5390)	2513 (5540)	2513 (5540)	2581 (5690)	2402 (5295)
	—	—	—	—	—	—
	—	—	—	—	—	—
30	3035 (6700)	3080 (6800)	3125 (6900)	3125 (6900)	3175 (7000)	3125 (6900)
	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	—	—	—	—	—	—
	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	180 (111)
	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	180 (111)
35	7.9, 7.8*3	8.0	8.3, 8.2*3	8.3, 8.2*3	8.4	7.1, 6.8*3
	16.1, 16.0*3	16.2	16.3	16.3	16.5	15.4, 15.3*3
	61 (37), 58 (36)*3	58 (36)	61 (37)*4, 58 (36) *3, 4, 23 (14)*5, 22 (13)*3, 5	61 (37)*4, 58 (36) *3, 4, 23 (14)*5, 22 (13)*3, 5	58 (36)*4, 22 (13)*5	62 (38), 59 (36)*3
	105 (65), 100 (62)*3	100 (62)	105 (65)*4, 100 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	105 (65)*4, 100 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	100 (62)*4, 38 (23)*5	106 (65), 101 (62)*3
	154 (95), 147 (91)*3	147 (91)	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	147 (91)*4, 56 (34)*5	154 (95), 147 (91)*3
40	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)
	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)
	—	—	—	—	—	180 (111)
	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)
	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)
45	2UZ-FE	2UZ-FE	2UZ-FE	2UZ-FE	2UZ-FE	3UR-FE
	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with Dual VVT-i
	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 102.0 (3.70 × 4.02)
	4664 (284.5)	4664 (284.5)	4664 (284.5)	4664 (284.5)	4664 (284.5)	5663 (345.6)
50	10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1	10.2 : 1
	SFI	SFI	SFI	SFI	SFI	SFI
	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
	202/5400 (271/5400)	202/5400 (271/5400)	202/5400 (271/5400)	202/5400 (271/5400)	202/5400 (271/5400)	284/5600 (381/5600)
	424/3400 (313/3400)	424/3400 (313/3400)	424/3400 (313/3400)	424/3400 (313/3400)	424/3400 (313/3400)	544/3600 (401/3600)
55	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	1200, 1560*3	1560	1200, 1560*3	1200, 1560*3	1560	1200, 1800*3
	1.4, 2.0*7	1.4, 2.0*7	1.4, 2.0*7	1.4, 2.0*7	1.4, 2.0*7	2.0
	—	—	—	—	—	—
	A750E (5A/T)	A750E (5A/T)	A750F (5A/T)	A750F (5A/T)	A750F (5A/T)	AB60E (6A/T)
60	3.520	3.520	3.520	3.520	3.520	3.333
	2.042	2.042	2.042	2.042	2.042	1.960
	1.400	1.400	1.400	1.400	1.400	1.353
	1.000	1.000	1.000	1.000	1.000	1.000
	0.716	0.716	0.716	0.716	0.716	0.728
65	—	—	—	—	—	0.588
	3.224	3.224	3.224	3.224	3.224	3.061
	—	—	1.000/2.618	1.000/2.618	1.000/2.618	—
	—/3.909, 4.100*3	—/4.100	3.909, 4.100*3/3.909, 4.100*3	3.909, 4.100*3/3.909, 4.100*3	4.100/4.100	—/4.100, 4.300*3
	—/241.3 (9.5)	—/241.3 (9.5)	220.0 (8.7)/241.3 (9.5)	220.0 (8.7)/241.3 (9.5)	220.0 (8.7)/241.3 (9.5)	—/266.7 (10.5)
70	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9	Tandem 8 + 9
	—	—	—	—	—	—
75	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
80	18 : 1	18 : 1	18 : 1	18 : 1	18 : 1	18 : 1
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item / Area				U.S.A.			
Cab Type				Double			
Vehicle Grade				Limited	SR5		Limited
Model Code				USK51L-CRTLKA	USK52L-CHTSKA	USK56L-CRTSKA	USK56L-CRTLKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2
	Wheel Base		mm (in.)	3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
	Cargo Space	Length	mm (in.)	2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	260 (10.2)	260 (10.2)	270 (10.6)	260 (10.2)
	Angle of Approach		degrees	28	28	29	29
	Angle of Departure		degrees	25, 20*3	20	25, 20*3	25, 20*3
	Curb Weight*6	Front	kg (lb)	1354 (2985)	1415 (3120)	1470 (3240)	1467 (3235)
		Rear	kg (lb)	1052 (2320)	1055 (2325)	1066 (2350)	1075 (2370)
		Total	kg (lb)	2406 (5305)	2470 (5445)	2536 (5590)	2542 (5605)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3125 (6900)	3175 (7000)	3220 (7100)	3220 (7100)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Acceleration	0 to 60 mph	sec.	7.1, 6.8*3	7.0	7.4, 7.1*3	7.4, 7.1*3
		0 to 400 m	sec.	15.4, 15.3*3	15.4	15.7, 15.6*3	15.7, 15.6*3
	Max. Permissible Speed	1st Gear	km/h (mph)	62 (38), 59 (36)*3	59 (36)	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
		2nd Gear	km/h (mph)	106 (65), 101 (62)*3	101 (62)	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
		3rd Gear	km/h (mph)	154 (95), 147 (91)*3	147 (91)	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
		4th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
		5th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
		6th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)
		Curb to Curb	m (ft.)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)
Engine	Engine Type			3UR-FE	3UR-FE	3UR-FE	3UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*7	12 - 64	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output		Watts	1560, 1800*3	1800	1200, 1800*3	1560, 1800*3
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			AB60E (6A/T)	AB60E (6A/T)	AB60F (6A/T)	AB60F (6A/T)
	Gear Ratio	In First		3.333	3.333	3.333	3.333
		In Second		1.960	1.960	1.960	1.960
		In Third		1.353	1.353	1.353	1.353
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.728	0.728	0.728	0.728
		In Sixth		0.588	0.588	0.588	0.588
		In Reverse		3.061	3.061	3.061	3.061
	Transfer Gear Ratio H4/L4			—	—	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			—/4.100, 4.300*3	—/4.300	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3
	Differential Gear Size (Front/Rear)		mm (in.)	—/266.7 (10.5)	—/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18 : 1	18 : 1	18 : 1	18 : 1
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: P255/70R18
*2: P275/65R18 or P275/55R20
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification

	U.S.A.					
	Double				Crew Max	
	SR5		Limited	SR5		Limited
	USK57L-CHTSKA	USK56L-CRTSGA	USK56L-CRTLGA	USK57L-CHTSGA	UCK51L-PSASKA	UCK51L-PSALKA
5	6290 (247.6)	5810 (228.7)	5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)
	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
	1935 (76.2)*1, 1930 (76.0)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1925 (75.8)*1, 1920 (75.6)*2	1920 (75.6)*2
	4180 (164.6)	3700 (145.7)	3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)
	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	983 (38.7)	983 (38.7)
	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	1131 (44.5)	1131 (44.5)
15	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1662 (65.4)	1662 (65.4)
	2480 (97.6)	2000 (78.7)	2000 (78.7)	2480 (97.6)	1695 (66.7)	1695 (66.7)
	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
20	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	270 (10.6)	270 (10.6)	260 (10.2)	270 (10.6)	260 (10.2)	255 (10.0)
	29	29	29	29	28	28
	20	25, 20*3	25, 20*3	20	25, 20*3	24, 19*3
25	1529 (3370)	1470 (3240)	1467 (3235)	1529 (3370)	1365 (3010)	1359 (2995)
	1068 (2355)	1066 (2350)	1075 (2370)	1068 (2355)	1082 (2385)	1091 (2405)
	2597 (5725)	2536 (5590)	2542 (5605)	2597 (5725)	2447 (5395)	2449 (5400)
	—	—	—	—	—	—
	—	—	—	—	—	—
30	3265 (7200)	3220 (7100)	3220 (7100)	3265 (7200)	3080 (6800)	3080 (6800)
	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	—	—	—	—	—	—
	170 (105)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	180 (111)	180 (111)
	170 (105)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	180 (111)	180 (111)
35	7.3	7.4, 7.1*3	7.4, 7.2*3	7.3	8.1, 8.0*3	8.1, 8.0*3
	15.7	15.7, 15.6*3	15.7, 15.6*3	15.7	16.2	16.2
	59 (36)*4, 22 (13)*5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)*4, 22 (13)*5	61 (37), 58 (36)*3	61 (37), 58 (36)*3
	101 (62)*4, 38 (23)*5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	101 (62)*4, 38 (23)*5	105 (65), 100 (62)*3	105 (65), 100 (62)*3
	147 (91)*4, 56 (34)*5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	147 (91)*4, 56 (34)*5	154 (95), 147 (91)*3	154 (95), 147 (91)*3
40	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)	180 (111)
	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)	180 (111)
	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	—	—
	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)
	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)
45	3UR-FE	3UR-FBE	3UR-FBE	3UR-FBE	2UZ-FE	2UZ-FE
	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i
	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)
	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	4664 (284.5)	4664 (284.5)
50	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.0 : 1	10.0 : 1
	SFI	SFI	SFI	SFI	SFI	SFI
	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	202/5400 (271/5400)	202/5400 (271/5400)
	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	424/3400 (313/3400)	424/3400 (313/3400)
55	12 - 64	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3	12 - 64	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	1800	1200, 1800*3	1560, 1800*3	1800	1200, 1560*3	1200, 1560*3
	2.0	2.0	2.0	2.0	1.4, 2.0*7	1.4, 2.0*7
	—	—	—	—	—	—
	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	A750E (5A/T)	A750E (5A/T)
60	3.333	3.333	3.333	3.333	3.520	3.520
	1.960	1.960	1.960	1.960	2.042	2.042
	1.353	1.353	1.353	1.353	1.400	1.400
	1.000	1.000	1.000	1.000	1.000	1.000
	0.728	0.728	0.728	0.728	0.716	0.716
65	0.588	0.588	0.588	0.588	—	—
	3.061	3.061	3.061	3.061	3.224	3.224
	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	—	—
	4.300/4.300	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.300/4.300	—/3.909, 4.100*3	—/3.909, 4.100*3
	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	—/241.3 (9.5)	—/241.3 (9.5)
70	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9
	—	—	—	—	—	—
75	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
80	18 : 1	18 : 1	18 : 1	18 : 1	18 : 1	18 : 1
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				U.S.A.			
Cab Type				Crew Max			
Vehicle Grade				SR5	Limited	SR5	Limited
Model Code				UCK56L-PSASKA	UCK56L-PSALKA	USK51L-PSTSKA	USK51L-PSTLKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2	1925 (75.8)*1, 1920 (75.6)*2	1920 (75.6)*2
	Wheel Base		mm (in.)	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
	Cargo Space	Length	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	265 (10.4)	265 (10.4)	260 (10.2)	255 (10.0)
	Angle of Approach		degrees	29	29	28	28
	Angle of Departure		degrees	25, 20*3	24, 19*3	25, 20*3	25, 20*3
	Curb Weight*6	Front	kg (lb)	1490 (3285)	1486 (3275)	1372 (3025)	1370 (3020)
		Rear	kg (lb)	1109 (2445)	1116 (2460)	1105 (2435)	1116 (2460)
		Total	kg (lb)	2599 (5730)	2601 (5735)	2477 (5460)	2486 (5480)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3175 (7000)	3175 (7000)	3175 (7000)	3175 (7000)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)
	Max. Cruising Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)
	Acceleration	0 to 60 mph	sec.	8.5	8.6, 8.5*3	7.3, 7.0*3	7.3, 7.0*3
		0 to 400 m	sec.	16.5	16.5	15.6, 15.4*3	15.6, 15.4*3
	Max. Permissible Speed	1st Gear	km/h (mph)	61 (37)*4, 58 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	61 (37)*4, 58 (36) *3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38), 59 (36)*3	62 (38), 59 (36)*3
		2nd Gear	km/h (mph)	105 (65)*4, 100 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	105 (65)*4, 100 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65), 101 (62)*3	106 (65), 101 (62)*3
		3rd Gear	km/h (mph)	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95), 147 (91)*3	154 (95), 147 (91)*3
		4th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	180 (111)
		5th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	180 (111)
		6th Gear	km/h (mph)	—	—	180 (111)	180 (111)
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
		Curb to Curb	m (ft.)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
Engine	Engine Type			2UZ-FE	2UZ-FE	3UR-FE	3UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	4664 (284.5)	4664 (284.5)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.0 : 1	10.0 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)*7		kW/rpm (HP/rpm)	202/5400 (271/5400)	202/5400 (271/5400)	284/5600 (381/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)*7		N·m/rpm (ft-lbf/rpm)	424/3400 (313/3400)	424/3400 (313/3400)	544/3600 (401/3600)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output		Watts	1200, 1560*3	1200, 1560*3	1200, 1560*8, 1800*3	1560, 1800*3
	Starter Output		kW	1.4, 2.0*7	1.4, 2.0*7	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A750F (5A/T)	A750F (5A/T)	AB60E (6A/T)	AB60E (6A/T)
	Gear Ratio	In First		3.520	3.520	3.333	3.333
		In Second		2.042	2.042	1.960	1.960
		In Third		1.400	1.400	1.353	1.353
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.716	0.716	0.728	0.728
		In Sixth		—	—	0.588	0.588
		In Reverse		3.224	3.224	3.061	3.061
	Transfer Gear Ratio H4/L4			1.000/2.618	1.000/2.618	—	—
	Differential Gear Ratio (Front/Rear)			3.909, 4.100*3/3.909, 4.100*3	3.909, 4.100*3/3.909, 4.100*3	—/4.100, 4.300*3	—/4.100, 4.300*3
	Differential Gear Size (Front/Rear)		mm (in.)	220.0 (8.7)/241.3 (9.5)	220.0 (8.7)/241.3 (9.5)	—/266.7 (10.5)	—/266.7 (10.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18 : 1	18 : 1	18 : 1	18 : 1
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: P255/70R18
*2: P275/65R18 or P275/55R20
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: With rear seat entertainment system

	U.S.A.			
	Crew Max			
	SR5	Limited	SR5	Limited
	USK56L-PSTSKA	USK56L-PSTLKA	USK56L-PSTSGA	USK56L-PSTLGA
5	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)
	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2
	3700 (145.7)	3700 (145.6)	3700 (145.7)	3700 (145.7)
	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
	983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
	1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
15	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
	1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
20	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	270 (10.6)	265 (10.4)	270 (10.6)	265 (10.4)
	29	28	29	28
	25, 20*3	25, 20*3	25, 20*3	25, 20*3
25	1486 (3275)	1483 (3270)	1486 (3275)	1483 (3270)
	1120 (2470)	1129 (2490)	1120 (2470)	1129 (2490)
	2606 (5745)	2613 (5760)	2606 (5745)	2613 (5760)
	—	—	—	—
	—	—	—	—
30	3265 (7200)	3265 (7200)	3265 (7200)	3265 (7200)
	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	—	—	—	—
	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
35	7.6, 7.3*3	7.6, 7.3*3	7.6, 7.3*3	7.6, 7.3*3
	15.9, 15.7*3	15.9, 15.7*3	15.9, 15.7*3	15.9, 15.7*3
	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
40	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
45	3UR-FE	3UR-FE	3UR-FBE	3UR-FBE
	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
50	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	SFI	SFI	SFI	SFI
	87 or higher	87 or higher	87 or higher	87 or higher
	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
55	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3
	1200, 1560*8, 1800*3	1560, 1800*3	1200, 1560*8, 1800*3	1560, 1800*3
	2.0	2.0	2.0	2.0
	—	—	—	—
	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)
60	3.333	3.333	3.333	3.333
	1.960	1.960	1.960	1.960
	1.353	1.353	1.353	1.353
	1.000	1.000	1.000	1.000
	0.728	0.728	0.728	0.728
65	0.588	0.588	0.588	0.588
	3.061	3.061	3.061	3.061
	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3
	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)	220.0 (8.7)/266.7 (10.5)
70	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9	Tundem 8 + 9
	—	—	—	—
75	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Standard	Standard	Standard	Standard
	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
80	18 : 1	18 : 1	18 : 1	18 : 1
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type