MAJOR TECHNICAL SPECIFICATIONS

Item / Area				U.S.A.			
Cab Type				Regular			
Vehicle Grade				Deluxe			
Model Code				GSK50L-TRADKA	GSK51L-THADKA	UPK50L-TRTDKA	UPK51L-THTDKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2
	Wheel Base		mm (in.)	3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	—	—	—	—
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	—	—	—	—
	Shoulder Room	Front	mm (in.)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)
		Rear	mm (in.)	—	—	—	—
	Cargo Space	**Length**	**mm (in.)**	2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	265 (10.4)	260 (10.2)	265 (10.4)	265 (10.4)
	Angle of Approach		degrees	27	28	27	27
	Angle of Departure		degrees	26	25	27, 22*3	26, 21*3
	Curb Weight*6	Front	kg (lb)	1169 (2575)	1208 (2665)	1230 (2710)	1273 (2805)
		Rear	kg (lb)	909 (2005)	916 (2020)	917 (2020)	919 (2025)
		Total	kg (lb)	2078 (4580)	2124 (4685)	2147 (4730)	2192 (4830)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	2810 (6200)	2900 (6400)	2990 (6600)	3080 (6800)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	—	—
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	—	—
	Acceleration	0 to 60 mph	sec.	8.4	8.6	—	—
		0 to 400 m	sec.	16.5	16.6	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	59 (36)	59 (36)	—	—
		2nd Gear	km/h (mph)	102 (63)	102 (63)	—	—
		3rd Gear	km/h (mph)	148 (91)	148 (91)	—	—
		4th Gear	km/h (mph)	180 (111)	180 (111)	—	—
		5th Gear	km/h (mph)	180 (111)	180 (111)	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)
		Curb to Curb	m (ft.)	11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)
Engine	Engine Type			1GR-FE	1GR-FE	1UR-FE	1UR-FE
	No. of Cyls. & Arrangement			6-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			24-valve DOHC with VVT-i	24-valve DOHC with VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	3956 (241.4)	4608 (281.2)	4608 (281.2)
	Compression Ratio			10.0 : 1	10.0 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			91 or higher	91 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	176/5200 (236/5200)	176/5200 (236/5200)	231/5600 (310/5600)	231/5600 (310/5600)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	361/4000 (266/4000)	361/4000 (266/4000)	443/3400 (327/3400)	443/3400 (327/3400)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*8	12 - 55, 12 - 64*8
	Generator Output		Watts	1200	1200	1200, 1800*3	1200, 1800*3
	Starter Output		kW	1.6, 2.0*7	1.6, 2.0*7	1.4, 2.0*7	1.4, 2.0*7
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A750E (5A/T)	A750E (5A/T)	A760E (6A/T)	A760E (6A/T)
	Gear Ratio	In 1st		3.520	3.520	3.520	3.520
		In 2nd		2.042	2.042	2.042	2.042
		In 3rd		1.400	1.400	1.400	1.400
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.716	0.716	0.716	0.716
		In 6th		—	—	0.586	0.586
		In Reverse		3.224	3.224	3.224	3.224
	Transfer Gear Ratio H4/L4			—	—	—	—
	Differential Gear Ratio (Front/Rear)			—/3.909	—/3.909	—/3.909, 4.100*3	—/3.909, 4.100*3
	Differential Gear Size (Front/Rear)		mm (in.)	—/240 (9.4)	—/240 (9.4)	—/240 (9.4)	—/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: Towing package or cold area specification

U.S.A.					
Regular					
Deluxe					
UPK55L-TRTDKA	UPK56L-THTDKA	USK50L-TRTDKA	USK51L-THTDKA	USK55L-TRTDKA	USK56L-THTDKA
5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2
3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
—	—	—	—	—	—
1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
—	—	—	—	—	—
1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)
—	—	—	—	—	—
2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)
1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
275 (10.8)	275 (10.8)	265 (10.4)	265 (10.4)	275 (10.8)	270 (10.6)
28	28	27	27	28	28
27, 22*3	27, 21*3	27, 22*3	26, 21*3	27, 22*3	26, 21*3
1340 (2955)	1388 (3060)	1259 (2775)	1290 (2845)	1362 (3005)	1399 (3085)
931 (2050)	929 (2050)	921 (2030)	936 (2065)	942 (2075)	951 (2095)
2271 (5005)	2317 (5110)	2180 (4805)	2226 (4910)	2304 (5080)	2350 (5180)
—	—	—	—	—	—
—	—	—	—	—	—
3080 (6800)	3175 (7000)	2990 (6600)	3175 (7000)	3080 (6800)	3265 (7200)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—	—	—	—
—	—	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
—	—	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
—	—	6.7, 6.4*3	6.8, 6.6*3	7.0, 6.7*3	7.1, 6.9*3
—	—	15.1, 14.9*3	15.2, 15.0*3	15.3, 15.2*3	15.5, 15.3*3
—	—	62 (38), 59 (36)*3	62 (38), 59 (36)*3	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
—	—	106 (65), 101 (62)*3	106 (65), 101 (62)*3	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
—	—	154 (95), 147 (91)*3	154 (95), 147 (91)*3	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
—	—	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
—	—	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
—	—	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)
11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)
1UR-FE	1UR-FE	3UR-FE	3UR-FE	3UR-FE	3UR-FE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
4608 (281.2)	4608 (281.2)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
231/5600 (310/5600)	231/5600 (310/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
443/3400 (327/3400)	443/3400 (327/3400)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
12 - 55, 12 - 64*8	12 - 55, 12 - 64*8	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
1200, 1800*3	1200, 1800*3	1200, 1800*3	1200, 1800*3	1200, 1800*3	1200, 1800*3
1.4, 2.0*7	1.4, 2.0*7	2.0	2.0	2.0	2.0
—	—	—	—	—	—
A760F (6A/T)	A760F (6A/T)	AB60E (6A/T)	AB60E (6A/T)	AB60F (6A/T)	AB60F (6A/T)
3.520	3.520	3.333	3.333	3.333	3.333
2.042	2.042	1.960	1.960	1.960	1.960
1.400	1.400	1.353	1.353	1.353	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.716	0.716	0.728	0.728	0.728	0.728
0.586	0.586	0.588	0.588	0.588	0.588
3.224	3.224	3.061	3.061	3.061	3.061
1.000/2.618	1.000/2.618	—	—	1.000/2.618	1.000/2.618
3.909, 4.100*3/3.909, 4.100*3	3.909, 4.100*3/3.909, 4.100*3	—/4.100, 4.300*3	—/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3
220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	—/265 (10.4)	—/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0	18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				U.S.A.			
Cab Type				Regular		Double	
Vehicle Grade				Deluxe		SR5	
Model Code				USK55L-TRTDGA	USK56L-THTDGA	GSK51L-CRASKA	UPK51L-CRTSKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5330 (209.8)	5810 (228.7)	5810 (228.7)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*1, 1925 (75.8)*2	1930 (76.0)*1, 1925 (75.8)*2
	Wheel Base		mm (in.)	3220 (126.8)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	—	—	982 (38.7)	982 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	—	—	882 (34.7)	882 (34.7)
	Shoulder Room	Front	mm (in.)	1694 (66.7)	1694 (66.7)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	—	—	1668 (65.7)	1668 (65.7)
	Cargo Space	**Length**	**mm (in.)**	2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	275 (10.8)	270 (10.6)	265 (10.4)	265 (10.4)
	Angle of Approach		degrees	28	28	28	28
	Angle of Departure		degrees	27, 22*3	25, 20*3	25	25, 20*3
	Curb Weight*6	Front	kg (lb)	1362 (3005)	1399 (3085)	1258 (2775)	1324 (2920)
		Rear	kg (lb)	942 (2075)	951 (2095)	986 (2175)	982 (2165)
		Total	kg (lb)	2304 (5080)	2350 (5180)	2244 (4950)	2306 (5085)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3080 (6800)	3265 (7200)	2900 (6400)	3035 (6700)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	—
	Max. Cruising Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	—
	Acceleration	0 to 60 mph	sec.	7.0, 6.7*3	7.1, 6.9*3	9.0	—
		0 to 400 m	sec.	15.3, 15.2*3	15.5, 15.3*3	16.9	—
	Max. Permissible Speed	1st Gear	km/h (mph)	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)	—
		2nd Gear	km/h (mph)	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	102 (63)	—
		3rd Gear	km/h (mph)	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	148 (91)	—
		4th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	—
		5th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	—
		6th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	12.88 (42.3)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
		Curb to Curb	m (ft.)	11.96 (39.2)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
Engine	Engine Type			3UR-FBE	3UR-FBE	1GR-FE	1UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	24-valve DOHC with VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 83.0 (3.70 × 3.27)
	Displacement		cm^3 (cu.in.)	5663 (345.6)	5663 (345.6)	3956 (241.4)	4608 (281.2)
	Compression Ratio			10.2 : 1	10.2 : 1	10.0 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	91 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	284/5600 (381/5600)	284/5600 (381/5600)	176/5200 (236/5200)	231/5600 (310/5600)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	544/3600 (401/3600)	544/3600 (401/3600)	361/4000 (266/4000)	443/3400 (327/3400)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3	12 - 55, 12 - 64*7	12 - 55, 12 - 64*8
	Generator Output		Watts	1200, 1800*3	1200, 1800*3	1200	1200, 1800*3
	Starter Output		kW	2.0	2.0	1.6, 2.0*7	1.4, 2.0*7
Chassis	Clutch Type			—	—	—	—
	Transmission Type			AB60F (6A/T)	AB60F (6A/T)	A750E (5A/T)	A760E (6A/T)
	Gear Ratio	In 1st		3.333	3.333	3.520	3.520
		In 2nd		1.960	1.960	2.042	2.042
		In 3rd		1.353	1.353	1.400	1.400
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.728	0.716	0.716
		In 6th		0.588	0.588	—	0.586
		In Reverse		3.061	3.061	3.224	3.224
	Transfer Gear Ratio H4/L4			1.000/2.618	1.000/2.618	—	—
	Differential Gear Ratio (Front/Rear)			4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	—/3.909	—/3.909, 4.100*3
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	—/240 (9.4)	—/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: Towing package or cold area specification

U.S.A.					
Double					
Limited	SR5		Limited	SR5	
UPK51L-CRTLKA	UPK52L-CHTSKA	UPK56L-CRTSKA	UPK56L-CRTLKA	UPK57L-CHTSKA	USK51L-CRTSKA
5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)	6290 (247.6)	5810 (228.7)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*1, 1925 (75.8)*2
3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)	4180 (164.6)	3700 (145.7)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)	2480 (97.6)	2000 (78.7)
1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
260 (10.2)	260 (10.2)	275 (10.8)	270 (10.6)	270 (10.6)	265 (10.4)
28	28	29	29	29	28
25, 20*3	20	25, 20*3	25, 20*3	20	25, 20*3
1330 (2930)	1383 (3050)	1447 (3190)	1453 (3210)	1511 (3330)	1340 (2955)
987 (2175)	1014 (2235)	996 (2195)	1001 (2210)	1023 (2255)	999 (2200)
2317 (5105)	2397 (5285)	2443 (5385)	2454 (5415)	2534 (5585)	2339 (5155)
—	—	—	—	—	—
—	—	—	—	—	—
3035 (6700)	3080 (6800)	3125 (6900)	3125 (6900)	3175 (7000)	3125 (6900)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—	—	—	—
—	—	—	—	—	180 (111)
—	—	—	—	—	180 (111)
—	—	—	—	—	7.1, 6.8*3
—	—	—	—	—	15.4, 15.3*3
—	—	—	—	—	62 (38), 59 (36)*3
—	—	—	—	—	106 (65), 101 (62)*3
—	—	—	—	—	154 (95), 147 (91)*3
—	—	—	—	—	180 (111)
—	—	—	—	—	180 (111)
—	—	—	—	—	180 (111)
14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)
13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)
1UR-FE	1UR-FE	1UR-FE	1UR-FE	1UR-FE	3UR-FE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)
4608 (281.2)	4608 (281.2)	4608 (281.2)	4608 (281.2)	4608 (281.2)	5663 (345.6)
10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
231/5600 (310/5600)	231/5600 (310/5600)	231/5600 (310/5600)	231/5600 (310/5600)	231/5600 (310/5600)	284/5600 (381/5600)
443/3400 (327/3400)	443/3400 (327/3400)	443/3400 (327/3400)	443/3400 (327/3400)	443/3400 (327/3400)	544/3600 (401/3600)
12 - 55, 12 - 64*8	12 - 64	12 - 55, 12 - 64*8	12 - 55, 12 - 64*8	12 - 64	12 - 55, 12 - 64*7
1560, 1800*3	1800	1200, 1800*3	1560, 1800*3	1800	1200, 1800*3
1.4, 2.0*7	1.4, 2.0*7	1.4, 2.0*7	1.4, 2.0*7	1.4, 2.0*7	2.0
—	—	—	—	—	—
A760E (6A/T)	A760E (6A/T)	A760F (6A/T)	A760F (6A/T)	A760F (6A/T)	AB60E (6A/T)
3.520	3.520	3.520	3.520	3.520	3.333
2.042	2.042	2.042	2.042	2.042	1.960
1.400	1.400	1.400	1.400	1.400	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.716	0.716	0.716	0.716	0.716	0.728
0.586	0.586	0.586	0.586	0.586	0.588
3.224	3.224	3.224	3.224	3.224	3.061
—	—	1.000/2.618	1.000/2.618	1.000/2.618	—
—/3.909, 4.100*3	—/4.100	3.909, 4.100*3/3.909, 4.100*3	3.909, 4.100*3/3.909, 4.100*3	4.100/4.100	—/4.100, 4.300*3
—/240 (9.4)	—/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	—/265 (10.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0	18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				U.S.A.			
Cab Type				Double			
Vehicle Grade				Limited	SR5		Limited
Model Code				USK51L-CRTLKA	USK52L-CHTSKA	USK56L-CRTSKA	USK56L-CRTLKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2
	Wheel Base		mm (in.)	3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
	Cargo Space	**Length**	**mm (in.)**	2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	260 (10.2)	260 (10.2)	270 (10.6)	260 (10.2)
	Angle of Approach		degrees	28	28	29	29
	Angle of Departure		degrees	25, 20*3	20	25, 20*3	25, 20*3
	Curb Weight*6	Front	kg (lb)	1345 (2965)	1400 (3085)	1456 (3210)	1461 (3220)
		Rear	kg (lb)	1004 (2215)	1030 (2270)	1020 (2250)	1025 (2260)
		Total	kg (lb)	2349 (5180)	2430 (5355)	2476 (5460)	2486 (5480)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3125 (6900)	3175 (7000)	3220 (7100)	3220 (7100)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Acceleration	0 to 60 mph	sec.	7.1, 6.8*3	7.0	7.4, 7.1*3	7.4, 7.1*3
		0 to 400 m	sec.	15.4, 15.3*3	15.4	15.7, 15.6*3	15.7, 15.6*3
	Max. Permissible Speed	1st Gear	km/h (mph)	62 (38), 59 (36)*3	59 (36)	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
		2nd Gear	km/h (mph)	106 (65), 101 (62)*3	101 (62)	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5,	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
		3rd Gear	km/h (mph)	154 (95), 147 (91)*3	147 (91)	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
		4th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
		5th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
		6th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)
		Curb to Curb	m (ft.)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)
Engine	Engine Type			3UR-FE	3UR-FE	3UR-FE	3UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*7	12 - 64	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output		Watts	1560, 1800*3	1800	1200, 1800*3	1560, 1800*3
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			AB60E (6A/T)	AB60E (6A/T)	AB60F (6A/T)	AB60F (6A/T)
	Gear Ratio	In 1st		3.333	3.333	3.333	3.333
		In 2nd		1.960	1.960	1.960	1.960
		In 3rd		1.353	1.353	1.353	1.353
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.728	0.728	0.728
		In 6th		0.588	0.588	0.588	0.588
		In Reverse		3.061	3.061	3.061	3.061
	Transfer Gear Ratio H4/L4			—	—	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			—/4.100, 4.300*3	—/4.300	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3
	Differential Gear Size (Front/Rear)		mm (in.)	—/265 (10.4)	—/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: Towing package or cold area specification
*9: Models with Rear Seat Entertainment (RSE) system except towing package

	U.S.A.					
	Double				CrewMax	
	SR5		Limited	SR5		Limited
	USK57L-CHTSKA	USK56L-CRTSGA	USK56L-CRTLGA	USK57L-CHTSGA	UPK51L-PSTSKA	UPK51L-PSTLKA
5	6290 (247.6)	5810 (228.7)	5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)
	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
	1935 (76.2)*1, 1930 (76.0)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1925 (75.8)*1, 1920 (75.6)*2	1920 (75.6)*2
	4180 (164.6)	3700 (145.7)	3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)
	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	983 (38.7)	983 (38.7)
	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	1131 (44.5)	1131 (44.5)
15	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1662 (65.4)	1662 (65.4)
	2480 (97.6)	2000 (78.7)	2000 (78.7)	2480 (97.6)	1695 (66.7)	1695 (66.7)
	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
20	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	270 (10.6)	270 (10.6)	260 (10.2)	270 (10.6)	260 (10.2)	255 (10.0)
	29	29	29	29	28	28
	20	25, 20*3	25, 20*3	20	25, 20*3	24, 19*3
25	1518 (3345)	1456 (3210)	1461 (3220)	1518 (3345)	1340 (2955)	1347 (2970)
	1049 (2315)	1020 (2250)	1025 (2260)	1049 (2315)	1041 (2295)	1045 (2305)
	2567 (5660)	2476 (5460)	2486 (5480)	2567 (5660)	2381 (5250)	2392 (5275)
	—	—	—	—	—	—
	—	—	—	—	—	—
30	3265 (7200)	3220 (7100)	3220 (7100)	3265 (7200)	3080 (6800)	3080 (6800)
	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	—	—	—	—	—	—
	170 (105)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	—	—
	170 (105)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	—	—
35	7.3	7.4, 7.1*3	7.4, 7.2*3	7.3	—	—
	15.7	15.7, 15.6*3	15.7, 15.6*3	15.7	—	—
	59 (36)*4, 22 (13)*5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)*4, 22 (13)*5	—	—
	101 (62)*4, 38 (23)*5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	101 (62)*4, 38 (23)*5	—	—
	147 (91)*4, 56 (34)*5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	147 (91)*4, 56 (34)*5	—	—
40	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	—	—
	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	—	—
	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	—	—
	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)
	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)
45	3UR-FE	3UR-FBE	3UR-FBE	3UR-FBE	1UR-FE	1UR-FE
	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)
	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	4608 (281.2)	4608 (281.2)
50	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	SFI	SFI	SFI	SFI	SFI	SFI
	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	231/5600 (310/5600)	231/5600 (310/5600)
	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	443/3400 (327/3400)	443/3400 (327/3400)
55	12 - 64	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3	12 - 64	12 - 55, 12 - 64*8	12 - 55, 12 - 64*8
	1800	1560, 1800*3	1560, 1800*3	1800	1200, 1800*3, 1560*9	1200, 1800*3, 1560*9
	2.0	2.0	2.0	2.0	1.4, 2.0*7	1.4, 2.0*7
	—	—	—	—	—	—
	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	A760E (6A/T)	A760E (6A/T)
60	3.333	3.333	3.333	3.333	3.520	3.520
	1.960	1.960	1.960	1.960	2.042	2.042
	1.353	1.353	1.353	1.353	1.400	1.400
	1.000	1.000	1.000	1.000	1.000	1.000
	0.728	0.728	0.728	0.728	0.716	0.716
65	0.588	0.588	0.588	0.588	0.586	0.586
	3.061	3.061	3.061	3.061	3.224	3.224
	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	—	—
	4.300/4.300	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.300/4.300	—/3.909, 4.100*3	—/3.909, 4.100*3
	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	—/240 (9.4)	—/240 (9.4)
70	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	—	—	—	—	—	—
75	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
80	18.0	18.0	18.0	18.0	18.0	18.0
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item / Area				U.S.A.			
Cab Type				CrewMax			
Vehicle Grade				SR5	Limited	SR5	Limited
Model Code				UPK56L-PSTSKA	UPK56L-PSTLKA	USK51L-PSTSKA	USK51L-PSTLKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2	1925 (75.8)*1, 1920 (75.6)*2	1920 (75.6)*2
	Wheel Base		mm (in.)	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
	Cargo Space	**Length**	**mm (in.)**	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	265 (10.4)	265 (10.4)	260 (10.2)	255 (10.0)
	Angle of Approach		degrees	29	29	28	28
	Angle of Departure		degrees	25, 20*3	24, 19*3	25, 20*3	25, 20*3
	Curb Weight*6	Front	kg (lb)	1463 (3225)	1472 (3245)	1356 (2990)	1362 (3005)
		Rear	kg (lb)	1055 (2325)	1062 (2340)	1063 (2345)	1067 (2350)
		Total	kg (lb)	2518 (5550)	2534 (5585)	2419 (5335)	2429 (5355)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3175 (7000)	3175 (7000)	3175 (7000)	3175 (7000)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	—	—	180 (111)	180 (111)
	Max. Cruising Speed		km/h (mph)	—	—	180 (111)	180 (111)
	Acceleration	0 to 60 mph	sec.	—	—	7.3, 7.0*3	7.3, 7.0*3
		0 to 400 m	sec.	—	—	15.6, 15.4*3	15.6, 15.4*3
	Max. Permissible Speed	1st Gear	km/h (mph)	—	—	62 (38), 59 (36)*3	62 (38), 59 (36)*3
		2nd Gear	km/h (mph)	—	—	106 (65), 101 (62)*3	106 (65), 101 (62)*3
		3rd Gear	km/h (mph)	—	—	154 (95), 147 (91)*3	154 (95), 147 (91)*3
		4th Gear	km/h (mph)	—	—	180 (111)	180 (111)
		5th Gear	km/h (mph)	—	—	180 (111)	180 (111)
		6th Gear	km/h (mph)	—	—	180 (111)	180 (111)
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
		Curb to Curb	m (ft.)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
Engine	Engine Type			1UR-FE	1UR-FE	3UR-FE	3UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	4608 (281.2)	4608 (281.2)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	231/5600 (310/5600)	231/5600 (310/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	443/3400 (327/3400)	443/3400 (327/3400)	544/3600 (401/3600)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*9	12 - 55, 12 - 64*9	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output		Watts	1200, 1800*3, 1560*10	1560, 1800*3	1200, 1560*8, 1800*3	1560, 1800*3
	Starter Output		kW	1.4, 2.0*7	1.4, 2.0*7	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A760F (6A/T)	A760F (6A/T)	AB60E (6A/T)	AB60E (6A/T)
	Gear Ratio	In 1st		3.520	3.520	3.333	3.333
		In 2nd		2.042	2.042	1.960	1.960
		In 3rd		1.400	1.400	1.353	1.353
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.716	0.716	0.728	0.728
		In 6th		0.586	0.586	0.588	0.588
		In Reverse		3.224	3.224	3.061	3.061
	Transfer Gear Ratio H4/L4			1.000/2.618	1.000/2.618	—	—
	Differential Gear Ratio (Front/Rear)			3.909, 4.100*3/3.909, 4.100*3	3.909, 4.100*3/3.909, 4.100*3	—/4.100, 4.300*3	—/4.100, 4.300*3
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	—/265 (10.4)	—/265 (10.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: Models with Rear Seat Entertainment (RSE) system
*9: Towing package or cold area specification
*10: Models with Rear Seat Entertainment (RSE) system except towing package

	U.S.A.			
	CrewMax			
	SR5	Limited	SR5	Limited
	USK56L-PSTSKA	USK56L-PSTLKA	USK56L-PSTSGA	USK56L-PSTLGA
5	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)
	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2
	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
	983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
	1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
15	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
	1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
20	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	270 (10.6)	265 (10.4)	270 (10.6)	265 (10.4)
	29	28	29	28
	25, 20*3	25, 20*3	25, 20*3	25, 20*3
25	1472 (3245)	1478 (3260)	1472 (3245)	1478 (3260)
	1079 (2380)	1083 (2385)	1079 (2380)	1083 (2385)
	2551 (5625)	2561 (5645)	2551 (5625)	2561 (5645)
	—	—	—	—
	—	—	—	—
30	3265 (7200)	3265 (7200)	3265 (7200)	3265 (7200)
	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	—	—	—	—
	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
35	7.6, 7.3*3	7.6, 7.3*3	7.6, 7.3*3	7.6, 7.3*3
	15.9, 15.7*3	15.9, 15.7*3	15.9, 15.7*3	15.9, 15.7*3
	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
40	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
45	3UR-FE	3UR-FE	3UR-FBE	3UR-FBE
	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
50	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	SFI	SFI	EFI	EFI
	87 or higher	87 or higher	87 or higher	87 or higher
	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
55	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3
	1200, 1560*8, 1800*3	—	1200, 1560*8, 1800*3	1560, 1800*3
	2.0	2.0	2.0	2.0
	—	—	—	—
	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)
60	3.333	3.333	3.333	3.333
	1.960	1.960	1.960	1.960
	1.353	1.353	1.353	1.353
	1.000	1.000	1.000	1.000
	0.728	0.728	0.728	0.728
65	0.588	0.588	0.588	0.588
	3.061	3.061	3.061	3.061
	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3
	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)
70	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	—	—	—	—
75	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Standard	Standard	Standard	Standard
	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
80	18.0	18.0	18.0	18.0
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type