MAJOR TECHNICAL SPECIFICATIONS

Item / Area				U.S.A.			
Cab Type				Regular			
Vehicle Grade				Deluxe			
Model Code				GSK50L-TRADKA	GSK51L-THADKA	UPK50L-TRTDKA	USK51L-THTDKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2
	Wheel Base		mm (in.)	3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	—	—	—	—
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	—	—	—	—
	Shoulder Room	Front	mm (in.)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)
		Rear	mm (in.)	—	—	—	—
	Cargo Space	**Length**	**mm (in.)**	2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	265 (10.4)	260 (10.2)	265 (10.4)	265 (10.4)
	Angle of Approach		degrees	27	28	27	27
	Angle of Departure		degrees	26	25	27, 22*3	26, 21*3
	Curb Weight*6	Front	kg (lb)	1169 (2575)	1208 (2665)	1230 (2710)	1290 (2845)
		Rear	kg (lb)	909 (2005)	916 (2020)	917 (2020)	936 (2065)
		Total	kg (lb)	2078 (4580)	2124 (4685)	2147 (4730)	2226 (4910)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	2810 (6200)	2900 (6400)	2990 (6600)	3175 (7000)
	Fuel Tank Capacity		L (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	—	180 (111)
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	—	180 (111)
	Acceleration	0 to 60 mph	sec.	8.4	8.6	—	6.8, 6.6*3
		0 to 400 m	sec.	16.5	16.6	—	15.2, 15.0*3
	Max. Permissible Speed	1st Gear	km/h (mph)	59 (36)	59 (36)	—	62 (38), 59 (36)*3
		2nd Gear	km/h (mph)	102 (63)	102 (63)	—	106 (65), 101 (62)*3
		3rd Gear	km/h (mph)	148 (91)	148 (91)	—	154 (95), 147 (91)*3
		4th Gear	km/h (mph)	180 (111)	180 (111)	—	180 (111)
		5th Gear	km/h (mph)	180 (111)	180 (111)	—	180 (111)
		6th Gear	km/h (mph)	—	—	—	180 (111)
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)
		Curb to Curb	m (ft.)	11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)
Engine	Engine Type			1GR-FE	1GR-FE	1UR-FE	3UR-FE
	No. of Cyls. & Arrangement			6-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			24-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	3956 (241.4)	4608 (281.2)	5663 (345.6)
	Compression Ratio			10.4 : 1	10.4 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	201/5600 (270/5600)	201/5600 (270/5600)	231/5600 (310/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	377/4400 (278/4400)	377/4400 (278/4400)	443/3400 (327/3400)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 55	12 - 55, 12 - 64*8	12 - 55, 12 - 64*7
	Generator Output		Watts	1200	1200	1200, 1800*3	1200, 1800*3
	Starter Output		kW	1.6, 1.4*7	1.6, 1.4*7	1.6, 2.0*7	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A750E (5A/T)	A750E (5A/T)	A760E (6A/T)	AB60E (6A/T)
	Gear Ratio	In 1st		3.520	3.520	3.520	3.333
		In 2nd		2.042	2.042	2.042	1.960
		In 3rd		1.400	1.400	1.400	1.353
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.716	0.716	0.716	0.728
		In 6th		—	—	0.586	0.588
		In Reverse		3.224	3.224	3.224	3.061
	Transfer Gear Ratio H4/L4			—	—	—	—
	Differential Gear Ratio (Front/Rear)			—/3.909	—/3.909	—/3.909, 4.100*3	—/4.100, 4.300*3
	Differential Gear Size (Front/Rear)		mm (in.)	—/240 (9.4)	—/240 (9.4)	—/240 (9.4)	—/265 (10.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: Towing package or cold area specification

U.S.A.					
Regular				Double	
Deluxe				SR5	
USK55L-TRTDKA	USK56L-THTDKA	USK55L-TRTDGA	USK56L-THTDGA	GSK51L-CRASKA	UPK51L-CRTSKA
5330 (209.8)	5810 (228.7)	5330 (209.8)	5810 (228.7)	5810 (228.7)	5810 (228.7)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*1, 1925 (75.8)*2	1930 (76.0)*1, 1925 (75.8)*2
3220 (126.8)	3700 (145.7)	3220 (126.8)	3700 (145.7)	3700 (145.7)	3700 (145.7)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
—	—	—	—	982 (38.7)	982 (38.7)
1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
—	—	—	—	882 (34.7)	882 (34.7)
1694 (66.7)	1694 (66.7)	1694 (66.7)	1694 (66.7)	1692 (66.6)	1692 (66.6)
—	—	—	—	1668 (65.7)	1668 (65.7)
2000 (78.7)	2480 (97.6)	2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)
1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
275 (10.8)	270 (10.6)	275 (10.8)	270 (10.6)	265 (10.4)	265 (10.4)
28	28	28	28	28	28
27, 22*3	26, 21*3	27, 22*3	25, 20*3	25	25, 20*3
1362 (3005)	1399 (3085)	1362 (3005)	1399 (3085)	1258 (2775)	1324 (2920)
942 (2075)	951 (2095)	942 (2075)	951 (2095)	986 (2175)	982 (2165)
2304 (5080)	2350 (5180)	2304 (5080)	2350 (5180)	2244 (4950)	2306 (5085)
—	—	—	—	—	—
—	—	—	—	—	—
3080 (6800)	3265 (7200)	3080 (6800)	3265 (7200)	2900 (6400)	3035 (6700)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—	—	—	—
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	—
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	—
7.0, 6.7*3	7.1, 6.9*3	7.0, 6.7*3	7.1, 6.9*3	9.0	—
15.3, 15.2*3	15.5, 15.3*3	15.3, 15.2*3	15.5, 15.3*3	16.9	—
62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)	—
106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	102 (63)	—
154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	148 (91)	—
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	—
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)	—
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—	—
12.88 (42.3)	14.36 (47.1)	12.88 (42.3)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
11.96 (39.2)	13.42 (44.0)	11.96 (39.2)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
3UR-FE	3UR-FE	3UR-FBE	3UR-FBE	1GR-FE	1UR-FE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type
32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 83.0 (3.70 × 3.27)
5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	3956 (241.4)	4608 (281.2)
10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.4 : 1	10.2 : 1
SFI	SFI	SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	201/5600 (270/5600)	231/5600 (310/5600)
544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	377/4400 (278/4400)	443/3400 (327/3400)
12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3	12 - 55	12 - 55, 12 - 64*8
1200, 1800*3	1200, 1800*3	1200, 1800*3	1200, 1800*3	1200	1200, 1800*3
2.0	2.0	2.0	2.0	1.6, 1.4*7	1.6, 2.0*7
—	—	—	—	—	—
AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	A750E (5A/T)	A760E (6A/T)
3.333	3.333	3.333	3.333	3.520	3.520
1.960	1.960	1.960	1.960	2.042	2.042
1.353	1.353	1.353	1.353	1.400	1.400
1.000	1.000	1.000	1.000	1.000	1.000
0.728	0.728	0.728	0.728	0.716	0.716
0.588	0.588	0.588	0.588	—	0.586
3.061	3.061	3.061	3.061	3.224	3.224
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	—	—
4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	—/3.909	—/3.909, 4.100*3
220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	—/240 (9.4)	—/240 (9.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0	18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				U.S.A.			
Cab Type				Double			
Vehicle Grade				SR5		LIMITED	SR5
Model Code				UPK56L-CRTSKA	USK51L-CRTSKA	USK51L-CRTLKA	USK52L-CHTSKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5810 (228.7)	5810 (228.7)	5810 (228.7)	6290 (247.6)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1940 (76.4)*1, 1935 (76.2)*2	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2
	Wheel Base		mm (in.)	3700 (145.7)	3700 (145.7)	3700 (145.7)	4180 (164.6)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
	Cargo Space	**Length**	**mm (in.)**	2000 (78.7)	2000 (78.7)	2000 (78.7)	2480 (97.6)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	275 (10.8)	265 (10.4)	260 (10.2)	260 (10.2)
	Angle of Approach		degrees	29	28	28	28
	Angle of Departure		degrees	25, 20*3	25, 20*3	25, 20*3	20
	Curb Weight*6	Front	kg (lb)	1447 (3190)	1340 (2955)	1345 (2965)	1400 (3085)
		Rear	kg (lb)	996 (2195)	999 (2200)	1004 (2215)	1030 (2270)
		Total	kg (lb)	2443 (5385)	2339 (5155)	2349 (5180)	2430 (5355)
	Gross Vehicle Weight*6	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3125 (6900)	3125 (6900)	3125 (6900)	3175 (7000)
	Fuel Tank Capacity		L (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	—	180 (111)	180 (111)	180 (111)
	Max. Cruising Speed		km/h (mph)	—	180 (111)	180 (111)	180 (111)
	Acceleration	0 to 60 mph	sec.	—	7.1, 6.8*3	7.1, 6.8*3	7.0
		0 to 400 m	sec.	—	15.4, 15.3*3	15.4, 15.3*3	15.4
	Max. Permissible Speed	1st Gear	km/h (mph)	—	62 (38), 59 (36)*3	62 (38), 59 (36)*3	59 (36)
		2nd Gear	km/h (mph)	—	106 (65), 101 (62)*3	106 (65), 101 (62)*3	101 (62)
		3rd Gear	km/h (mph)	—	154 (95), 147 (91)*3	154 (95), 147 (91)*3	147 (91)
		4th Gear	km/h (mph)	—	180 (111)	180 (111)	180 (111)
		5th Gear	km/h (mph)	—	180 (111)	180 (111)	180 (111)
		6th Gear	km/h (mph)	—	180 (111)	180 (111)	180 (111)
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)
		Curb to Curb	m (ft.)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)
Engine	Engine Type			1UR-FE	3UR-FE	3UR-FE	3UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke		mm (in.)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	4608 (281.2)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	231/5600 (310/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	443/3400 (327/3400)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*8	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 64
	Generator Output		Watts	1200, 1800*3	1200, 1800*3	1560, 1800*3	1800
	Starter Output		kW	1.6, 2.0*7	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A760F (6A/T)	AB60E (6A/T)	AB60E (6A/T)	AB60E (6A/T)
	Gear Ratio	In 1st		3.520	3.333	3.333	3.333
		In 2nd		2.042	1.960	1.960	1.960
		In 3rd		1.400	1.353	1.353	1.353
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.716	0.728	0.728	0.728
		In 6th		0.586	0.588	0.588	0.588
		In Reverse		3.224	3.061	3.061	3.061
	Transfer Gear Ratio H4/L4			1.000/2.618	—	—	—
	Differential Gear Ratio (Front/Rear)			3.909, 4.100*3/3.909, 4.100*3	—/4.100, 4.300*3	—/4.100, 4.300*3	—/4.300
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	—/265 (10.4)	—/265 (10.4)	—/265 (10.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: Towing package or cold area specification

U.S.A.					
Double					
SR5	LIMITED	SR5		LIMITED	SR5
USK56L-CRTSKA	USK56L-CRTLKA	USK57L-CHTSKA	USK56L-CRTSGA	USK56L-CRTLGA	USK57L-CHTSGA
5810 (228.7)	5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)	6290 (247.6)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2
3700 (145.7)	3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)	4180 (164.6)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
2000 (78.7)	2000 (78.7)	2480 (97.6)	2000 (78.7)	2000 (78.7)	2480 (97.6)
1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
270 (10.6)	260 (10.2)	270 (10.6)	270 (10.6)	260 (10.2)	270 (10.6)
29	29	29	29	29	29
25, 20*3	25, 20*3	20	25, 20*3	25, 20*3	20
1456 (3210)	1461 (3220)	1518 (3345)	1456 (3210)	1461 (3220)	1518 (3345)
1020 (2250)	1025 (2260)	1049 (2315)	1020 (2250)	1025 (2260)	1049 (2315)
2476 (5460)	2486 (5480)	2567 (5660)	2476 (5460)	2486 (5480)	2567 (5660)
—	—	—	—	—	—
—	—	—	—	—	—
3220 (7100)	3220 (7100)	3265 (7200)	3220 (7100)	3220 (7100)	3265 (7200)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—	—	—	—
180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)
180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	170 (105)
7.4, 7.1*3	7.4, 7.1*3	7.3	7.4, 7.1*3	7.4, 7.2*3	7.3
15.7, 15.6*3	15.7, 15.6*3	15.7	15.7, 15.6*3	15.7, 15.6*3	15.7
62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)*4, 22 (13)*5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)*4, 22 (13)*5
106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	101 (62)*4, 38 (23)*5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	101 (62)*4, 38 (23)*5
154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	147 (91)*4, 56 (34)*5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	147 (91)*4, 56 (34)*5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5
14.36 (47.1)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)
13.42 (44.0)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)
3UR-FE	3UR-FE	3UR-FE	3UR-FBE	3UR-FBE	3UR-FBE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 64	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3	12 - 64
1200, 1800*3	1560, 1800*3	1800	1200, 1800*3	1560, 1800*3	1800
2.0	2.0	2.0	2.0	2.0	2.0
—	—	—	—	—	—
AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)
3.333	3.333	3.333	3.333	3.333	3.333
1.960	1.960	1.960	1.960	1.960	1.960
1.353	1.353	1.353	1.353	1.353	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.728	0.728	0.728	0.728	0.728	0.728
0.588	0.588	0.588	0.588	0.588	0.588
3.061	3.061	3.061	3.061	3.061	3.061
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.300/4.300	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.300/4.300
220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0	18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item / Area			U.S.A.			
Cab Type			CrewMax			
Vehicle Grade			SR5			LIMITED
Model Code			UPK51L-PSTSKA	UPK56L-PSTSKA	USK51L-PSTSKA	USK51L-PSTLKA
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)
		Width mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height mm (in.)	1925 (75.8)*1, 1920 (75.6)*2	1935 (76.2)*1, 1930 (76.0)*2	1925 (75.8)*1, 1920 (75.6)*2	1920 (75.6)*2
	Wheel Base	mm (in.)	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	Tread	Front mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear mm (in.)	983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
	Effective Leg Room	Front mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear mm (in.)	1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
	Shoulder Room	Front mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear mm (in.)	1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
	Cargo Space	**Length mm (in.)**	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Width mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance	mm (in.)	260 (10.2)	265 (10.4)	260 (10.2)	255 (10.0)
	Angle of Approach	degrees	28	29	28	28
	Angle of Departure	degrees	25, 20*3	25, 20*3	25, 20*3	25, 20*3
	Curb Weight*6	Front kg (lb)	1340 (2955)	1463 (3225)	1356 (2990)	1362 (3005)
		Rear kg (lb)	1041 (2295)	1055 (2325)	1063 (2345)	1067 (2350)
		Total kg (lb)	2381 (5250)	2518 (5550)	2419 (5335)	2429 (5355)
	Gross Vehicle Weight*6	Front kg (lb)	—	—	—	—
		Rear kg (lb)	—	—	—	—
		Total kg (lb)	3080 (6800)	3175 (7000)	3175 (7000)	3175 (7000)
	Fuel Tank Capacity	L (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity	m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed	km/h (mph)	—	—	180 (111)	180 (111)
	Max. Cruising Speed	km/h (mph)	—	—	180 (111)	180 (111)
	Acceleration	0 to 60 mph sec.	—	—	7.3, 7.0*3	7.3, 7.0*3
		0 to 400 m sec.	—	—	15.6, 15.4*3	15.6, 15.4*3
	Max. Permissible Speed	1st Gear km/h (mph)	—	—	62 (38), 59 (36)*3	62 (38), 59 (36)*3
		2nd Gear km/h (mph)	—	—	106 (65), 101 (62)*3	106 (65), 101 (62)*3
		3rd Gear km/h (mph)	—	—	154 (95), 147 (91)*3	154 (95), 147 (91)*3
		4th Gear km/h (mph)	—	—	180 (111)	180 (111)
		5th Gear km/h (mph)	—	—	180 (111)	180 (111)
		6th Gear km/h (mph)	—	—	180 (111)	180 (111)
	Turning Diameter (Outside Front)	Wall to Wall m (ft.)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
		Curb to Curb m (ft.)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
Engine	Engine Type		1UR-FE	1UR-FE	3UR-FE	3UR-FE
	No. of Cyls. & Arrangement		8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism		32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke	mm (in.)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement	cm^3 (cu.in.)	4608 (281.2)	4608 (281.2)	5663 (345.6)	5663 (345.6)
	Compression Ratio		10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System		SFI	SFI	SFI	SFI
	Octane Rating		87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)	kW/rpm (HP/rpm)	231/5600 (310/5600)	231/5600 (310/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)	N·m/rpm (ft-lbf/rpm)	443/3400 (327/3400)	443/3400 (327/3400)	544/3600 (401/3600)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)	Voltage & Amp. hr.	12 - 55, 12 - 64*9	12 - 55, 12 - 64*9	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output	Watts	1200, 1800*3, 1560*10	1200, 1800*3, 1560*10	1200, 1560*8, 1800*3	1560, 1800*3
	Starter Output	kW	1.6, 2.0*7	1.6, 2.0*7	2.0	2.0
Chassis	Clutch Type		—	—	—	—
	Transmission Type		A760E (6A/T)	A760F (6A/T)	AB60E (6A/T)	AB60E (6A/T)
	Gear Ratio	In 1st	3.520	3.520	3.333	3.333
		In 2nd	2.042	2.042	1.960	1.960
		In 3rd	1.400	1.400	1.353	1.353
		In 4th	1.000	1.000	1.000	1.000
		In 5th	0.716	0.716	0.728	0.728
		In 6th	0.586	0.586	0.588	0.588
		In Reverse	3.224	3.224	3.061	3.061
	Transfer Gear Ratio H4/L4		—	1.000/2.618	—	—
	Differential Gear Ratio (Front/Rear)		—/3.909, 4.100*3	3.909, 4.100*3/3.909, 4.100*3	—/4.100, 4.300*3	—/4.100, 4.300*3
	Differential Gear Size (Front/Rear)	mm (in.)	—/240 (9.4)	220 (8.7)/240 (9.4)	—/265 (10.4)	—/265 (10.4)
	Brake Type	Front	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type		Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size	in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type		—	—	—	—
	Suspension Type	Front	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front	Standard	Standard	Standard	Standard
		Rear	—	—	—	—
	Steering Gear Type		Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)		18.0	18.0	18.0	18.0
	Power Steering Type		Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: kg is an approximate value.
*7: Cold area specification
*8: Models with Rear Seat Entertainment (RSE) system
*9: Towing package or cold area specification
*10: Models with Rear Seat Entertainment (RSE) system except towing package

U.S.A.			
CrewMax			
SR5	LIMITED	SR5	LIMITED
USK56L-PSTSKA	USK56L-PSTLKA	USK56L-PSTSGA	USK56L-PSTLGA
5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2
3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
270 (10.6)	265 (10.4)	270 (10.6)	265 (10.4)
29	28	29	28
25, 20*3	25, 20*3	25, 20*3	25, 20*3
1472 (3245)	1478 (3260)	1472 (3245)	1478 (3260)
1079 (2380)	1083 (2385)	1079 (2380)	1083 (2385)
2551 (5625)	2561 (5645)	2551 (5625)	2561 (5645)
—	—	—	—
—	—	—	—
3265 (7200)	3265 (7200)	3265 (7200)	3265 (7200)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—	—
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
7.6, 7.3*3	7.6, 7.3*3	7.6, 7.3*3	7.6, 7.3*3
15.9, 15.7*3	15.9, 15.7*3	15.9, 15.7*3	15.9, 15.7*3
62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
3UR-FE	3UR-FE	3UR-FBE	3UR-FBE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher
284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*3	12 - 55, 12 - 64*3
1200, 1560*8, 1800*3	1560, 1800*3	1200, 1560*8, 1800*3	1560, 1800*3
2.0	2.0	2.0	2.0
—	—	—	—
AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)
3.333	3.333	3.333	3.333
1.960	1.960	1.960	1.960
1.353	1.353	1.353	1.353
1.000	1.000	1.000	1.000
0.728	0.728	0.728	0.728
0.588	0.588	0.588	0.588
3.061	3.061	3.061	3.061
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3	4.100, 4.300*3/4.100, 4.300*3
220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)	220 (8.7)/265 (10.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
Standard	Standard	Standard	Standard
—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type