MAJOR TECHNICAL SPECIFICATIONS

Item / Area				U.S.A.			
Cab Type				Regular			
Vehicle Grade				SR5			
Model Code				GSK51L-THASKA	USK51L-THTSKA	USK56L-THTSKA	USK56L-THTSGA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Wheel Base		mm (in.)	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	—	—	—	—
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	—	—	—	—
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	—	—	—	—
	Cargo Space	Length	mm (in.)	2480 (97.6)	2480 (97.6)	2480 (97.6)	2480 (97.6)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	—	—	—	—
		Rear	mm (in.)	—	—	—	—
	Min. Running Ground Clearance		mm (in.)	—	—	—	—
	Angle of Approach		degrees	—	—	—	—
	Angle of Departure		degrees	—	—	—	—
	Curb Weight	Front	kg (lb)	1216 (2680)	1315 (2900)	1415 (3120)	1415 (3120)
		Rear	kg (lb)	943 (2080)	991 (2185)	1007 (2220)	1007 (2220)
		Total	kg (lb)	2159 (4760)	2307 (5085)	2422 (5340)	2422 (5340)
	Gross Vehicle Weight	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	2903 (6400)	3175 (7000)	3266 (7200)	3266 (7200)
	Fuel Tank Capacity		L (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Acceleration	0 to 60 mph	sec.	—	—	—	—
		0 to 400 m	sec.	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	—	—	—
		2nd Gear	km/h (mph)	—	—	—	—
		3rd Gear	km/h (mph)	—	—	—	—
		4th Gear	km/h (mph)	—	—	—	—
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	—	—	—	—
		Curb to Curb	m (ft.)	—	—	—	—
Engine	Engine Type			1GR-FE	3UR-FE	3UR-FE	3UR-FBE
	No. of Cyls. & Arrangement			6-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			24-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.4 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW@rpm (HP@rpm)	201@5600 (270@5600)	284@5600 (381@5600)	284@5600 (381@5600)	284@5600 (381@5600)
	Max. Torque (SAE-NET)		N·m@rpm (ft-lbf@rpm)	377@4400 (278@4400)	544@3600 (401@3600)	544@3600 (401@3600)	544@3600 (401@3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 55, 12 - 64*5	12 - 55, 12 - 64*5	12 - 55, 12 - 64*5
	Generator Output		Watts	1200	1200, 1800*3	1200, 1800*3	1200, 1800*3
	Starter Output		kW	1.6, 1.4*4	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A750E (5A/T)	AB60E (6A/T)	AB60F (6A/T)	AB60F (6A/T)
	Gear Ratio	In 1st		3.520	3.333	3.333	3.333
		In 2nd		2.042	1.960	1.960	1.960
		In 3rd		1.400	1.353	1.353	1.353
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.716	0.728	0.728	0.728
		In 6th		—	0.588	0.588	0.588
		In Reverse		3.224	3.061	3.061	3.061
	Transfer Gear Ratio High/Low			—	—	1.000/2.640	1.000/2.640
	Differential Gear Ratio	Front		—	—	4.100, 4.300*3	4.100, 4.300*3
		Rear		3.909	4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
	Differential Gear Size	Front	mm (in.)	—	—	220 (8.7)	220 (8.7)
		Rear	mm (in.)	241 (9.5)	267 (10.5)	267 (10.5)	267 (10.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Cold area specification
*5: Towing package or cold area specification

	U.S.A.					
	Double					
	SR5				LIMITED	SR5
	GSK51L-CRASKA	UPK51L-CRTSKA	UPK56L-CRTSKA	USK51L-CRTSKA	USK51L-CRTLKA	USK52L-CHTSKA
5	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)	6290 (247.6)
	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
	1930 (76.0)	1930 (76.0)*1, 1925 (75.8)*2	1940 (76.4)*1, 1935 (76.2)*2	1930 (76.0)*1, 1925 (75.8)*2	1930 (76.0)*1, 1925 (75.8)*2	1925 (75.8)*1, 1920 (75.6)*2
	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)	4180 (164.6)
	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
15	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
	2000 (78.7)	2000 (78.7)	2000 (78.7)	2000 (78.7)	2000 (78.7)	2480 (97.6)
	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
20	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	265 (10.4)	265 (10.4)	275 (10.8)	265 (10.4)	260 (10.2)	260 (10.2)
	28	28	29	28	28	28
	25	25, 20*3	25, 20*3	25, 20*3	25, 20*3	20
25	1266 (2790)	1340 (2955)	1456 (3210)	1365 (3010)	1377 (3035)	1427 (3145)
	1007 (2220)	1036 (2285)	1055 (2325)	1048 (2310)	1061 (2340)	1068 (2355)
	2273 (5010)	2377 (5240)	2511 (5535)	2413 (5320)	2438 (5375)	2495 (5500)
	—	—	—	—	—	—
	—	—	—	—	—	—
30	2903 (6400)	3039 (6700)	3130 (6900)	3130 (6900)	3130 (6900)	3175 (7000)
	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	—	—	—	—	—	—
	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)
	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)
35	9.0	—	—	7.1, 6.8*3	7.1, 6.8*3	7.0
	16.9	—	—	15.4, 15.3*3	15.4, 15.3*3	15.4
	59 (36)	—	—	62 (38), 59 (36)*3	62 (38), 59 (36)*3	59 (36)
	102 (63)	—	—	106 (65), 101 (62)*3	106 (65), 101 (62)*3	101 (62)
	148 (91)	—	—	154 (95), 147 (91)*3	154 (95), 147 (91)*3	147 (91)
40	180 (111)	—	—	180 (111)	180 (111)	180 (111)
	180 (111)	—	—	180 (111)	180 (111)	180 (111)
	—	—	—	180 (111)	180 (111)	180 (111)
	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)
	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)
45	1GR-FE	1UR-FE	1UR-FE	3UR-FE	3UR-FE	3UR-FE
	6-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	24-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	94.0 × 95.0 (3.70 × 3.74)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	3956 (241.4)	4608 (281.2)	4608 (281.2)	5663 (345.6)	5663 (345.6)	5663 (345.6)
50	10.4 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	SFI	SFI	SFI	SFI	SFI	SFI
	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
	201@5600 (270@5600)	231@5600 (310@5600)	231@5600 (310@5600)	284@5600 (381@5600)	284@5600 (381@5600)	284@5600 (381@5600)
	377@4400 (278@4400)	443@3400 (327@3400)	443@3400 (327@3400)	544@3600 (401@3600)	544@3600 (401@3600)	544@3600 (401@3600)
55	12 - 55	12 - 55, 12 - 64*5	12 - 55, 12 - 64*5	12 - 55, 12 - 64*5	12 - 55, 12 - 64*5	12 - 55, 12 - 64*5
	1200	1200, 1800*3	1200, 1800*3	1200, 1800*3	1560, 1800*3	1200, 1800*3
	1.6, 1.4*4	1.6, 2.0*4	1.6, 2.0*4	2.0	2.0	2.0
	—	—	—	—	—	—
	A750E (5A/T)	A760E (6A/T)	A760F (6A/T)	AB60E (6A/T)	AB60E (6A/T)	AB60E (6A/T)
60	3.520	3.520	3.520	3.333	3.333	3.333
	2.042	2.042	2.042	1.960	1.960	1.960
	1.400	1.400	1.400	1.353	1.353	1.353
	1.000	1.000	1.000	1.000	1.000	1.000
	0.716	0.716	0.716	0.728	0.728	0.728
65	—	0.586	0.586	0.588	0.588	0.588
	3.224	3.224	3.224	3.061	3.061	3.061
	—	—	1.000/2.640	—	—	—
	—	—	3.909	—	—	—
	3.909	3.909	3.909	4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
70	—	—	220 (8.7)	—	—	—
	241 (9.5)	241 (9.5)	241 (9.5)	267 (10.5)	267 (10.5)	267 (10.5)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
75	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	—	—	—	—	—	—
	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Standard	Standard	Standard	Standard	Standard	Standard
80	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	18.0	18.0	18.0	18.0	18.0	18.0
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item / Area				U.S.A.			
Cab Type				Double			
Vehicle Grade				SR5	LIMITED	SR5	
Model Code				USK56L-CRTSKA	USK56L-CRTLKA	USK57L-CHTSKA	USK56L-CRTSGA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5810 (228.7)	5810 (228.7)	6290 (247.6)	5810 (228.7)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1940 (76.4)*1, 1935 (76.2)*2
	Wheel Base		mm (in.)	3700 (145.7)	3700 (145.7)	4180 (164.6)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	982 (38.7)	982 (38.7)	982 (38.7)	982 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	882 (34.7)	882 (34.7)	882 (34.7)	882 (34.7)
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	1668 (65.7)	1668 (65.7)	1668 (65.7)	1668 (65.7)
	Cargo Space	Length	mm (in.)	2000 (78.7)	2000 (78.7)	2480 (97.6)	2000 (78.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	270 (10.6)	260 (10.2)	270 (10.6)	270 (10.6)
	Angle of Approach		degrees	29	29	29	29
	Angle of Departure		degrees	25, 20*3	25, 20*3	20	25, 20*3
	Curb Weight	Front	kg (lb)	1474 (3250)	1483 (3270)	1529 (3370)	1474 (3250)
		Rear	kg (lb)	1077 (2375)	1091 (2405)	1082 (2385)	1077 (2375)
		Total	kg (lb)	2552 (5625)	2574 (5675)	2610 (5755)	2552 (5625)
	Gross Vehicle Weight	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3221 (7100)	3221 (7100)	3266 (7200)	3221 (7100)
	Fuel Tank Capacity		L (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Max. Cruising Speed		km/h (mph)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Acceleration	0 to 60 mph	sec.	7.4, 7.1*3	7.4, 7.1*3	7.3	7.4, 7.1*3
		0 to 400 m	sec.	15.7, 15.6*3	15.7, 15.6*3	15.7	15.7, 15.6*3
	Max. Permissible Speed	1st Gear	km/h (mph)	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)*4, 22 (13)*5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5
		2nd Gear	km/h (mph)	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	101 (62)*4, 38 (23)*5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5
		3rd Gear	km/h (mph)	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	147 (91)*4, 56 (34)*5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5
		4th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
		5th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
		6th Gear	km/h (mph)	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	14.36 (47.1)	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)
		Curb to Curb	m (ft.)	13.42 (44.0)	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)
Engine	Engine Type			3UR-FE	3UR-FE	3UR-FE	3UR-FBE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW@rpm (HP@rpm)	284@5600 (381@5600)	284@5600 (381@5600)	284@5600 (381@5600)	284@5600 (381@5600)
	Max. Torque (SAE-NET)		N·m@rpm (ft-lbf@rpm)	544@3600 (401@3600)	544@3600 (401@3600)	544@3600 (401@3600)	544@3600 (401@3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	Generator Output		Watts	1200, 1800*3	1560, 1800*3	1200, 1800*3	1200, 1800*3
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)
	Gear Ratio	In 1st		3.333	3.333	3.333	3.333
		In 2nd		1.960	1.960	1.960	1.960
		In 3rd		1.353	1.353	1.353	1.353
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.728	0.728	0.728
		In 6th		0.588	0.588	0.588	0.588
		In Reverse		3.061	3.061	3.061	3.061
	Transfer Gear Ratio High/Low			1.000/2.640	1.000/2.640	1.000/2.640	1.000/2.640
	Differential Gear Ratio	Front		4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
		Rear		4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
	Differential Gear Size	Front	mm (in.)	220 (8.7)	220 (8.7)	220 (8.7)	220 (8.7)
		Rear	mm (in.)	267 (10.5)	267 (10.5)	267 (10.5)	267 (10.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: Cold area specification
*7: Towing package or cold area specification

	U.S.A.					
	Double		CrewMax			
	LIMITED	SR5	SR5			LIMITED
	USK56L-CRTLGA	USK57L-CHTSGA	UPK51L-PSTSKA	UPK56L-PSTSKA	USK51L-PSTSKA	USK51L-PSTLKA
5	5810 (228.7)	6290 (247.6)	5810 (228.7)	5810 (228.7)	5810 (228.7)	5810 (228.7)
	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
	1940 (76.4)*1, 1935 (76.2)*2	1935 (76.2)*1, 1930 (76.0)*2	1925 (75.8)*1, 1920 (75.6)*2	1935 (76.2)*1, 1930 (76.0)*2	1925 (75.8)*1, 1920 (75.6)*2	1920 (75.6)*2
	3700 (145.7)	4180 (164.6)	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
	982 (38.7)	982 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
	882 (34.7)	882 (34.7)	1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
15	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
	1668 (65.7)	1668 (65.7)	1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
	2000 (78.7)	2480 (97.6)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
20	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	260 (10.2)	270 (10.6)	260 (10.2)	265 (10.4)	260 (10.2)	255 (10.0)
	29	29	28	29	28	28
	25, 20*3	20	25, 20*3	25, 20*3	25, 20*3	25, 20*3
25	1483 (3270)	1529 (3370)	1356 (2990)	1472 (3245)	1379 (3040)	1395 (3075)
	1091 (2405)	1082 (2385)	1086 (2395)	1102 (2430)	1107 (2440)	1132 (2495)
	2574 (5675)	2610 (5755)	2443 (5385)	2574 (5675)	2486 (5480)	2527 (5570)
	—	—	—	—	—	—
	—	—	—	—	—	—
30	3221 (7100)	3266 (7200)	3084 (6800)	3175 (7000)	3175 (7000)	3175 (7000)
	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	—	—	—	—	—	—
	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)	180 (111)	180 (111)
	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111)	180 (111)	180 (111)	180 (111)
35	7.4, 7.2*3	7.3	—	—	7.3, 7.0*3	7.3, 7.0*3
	15.7, 15.6*3	15.7	—	—	15.6, 15.4*3	15.6, 15.4*3
	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	59 (36)*4, 22 (13)*5	—	—	62 (38), 59 (36)*3	62 (38), 59 (36)*3
	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	101 (62)*4, 38 (23)*5	—	—	106 (65), 101 (62)*3	106 (65), 101 (62)*3
	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	147 (91)*4, 56 (34)*5	—	—	154 (95), 147 (91)*3	154 (95), 147 (91)*3
40	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	—	—	180 (111)	180 (111)
	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	—	—	180 (111)	180 (111)
	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	170 (105)*4, 64 (39)*5	—	—	180 (111)	180 (111)
	14.36 (47.1)	15.86 (52.0)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)	14.36 (47.1)
	13.42 (44.0)	14.92 (49.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)	13.42 (44.0)
45	3UR-FBE	3UR-FBE	1UR-FE	1UR-FE	3UR-FE	3UR-FE
	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	5663 (345.6)	5663 (345.6)	4608 (281.2)	4608 (281.2)	5663 (345.6)	5663 (345.6)
50	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	SFI	SFI	SFI	SFI	SFI	SFI
	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
	284@5600 (381@5600)	284@5600 (381@5600)	231@5600 (310@5600)	231@5600 (310@5600)	284@5600 (381@5600)	284@5600 (381@5600)
	544@3600 (401@3600)	544@3600 (401@3600)	443@3400 (327@3400)	443@3400 (327@3400)	544@3600 (401@3600)	544@3600 (401@3600)
55	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7	12 - 55, 12 - 64*7
	1560, 1800*3	1200, 1800*3	1200, 1800*3	1200, 1800*3	1200, 1800*3	1560, 1800*3
	2.0	2.0	1.6, 2.0*6	1.6, 2.0*6	2.0	2.0
	—	—	—	—	—	—
	AB60F (6A/T)	AB60F (6A/T)	A760E (6A/T)	A760F (6A/T)	AB60E (6A/T)	AB60E (6A/T)
60	3.333	3.333	3.520	3.520	3.333	3.333
	1.960	1.960	2.042	2.042	1.960	1.960
	1.353	1.353	1.400	1.400	1.353	1.353
	1.000	1.000	1.000	1.000	1.000	1.000
	0.728	0.728	0.716	0.716	0.728	0.728
65	0.588	0.588	0.586	0.586	0.588	0.588
	3.061	3.061	3.224	3.224	3.061	3.061
	1.000/2.640	1.000/2.640	—	1.000/2.640	—	—
	4.100, 4.300*3	4.100, 4.300*3	—	3.909	—	—
	4.100, 4.300*3	4.100, 4.300*3	3.909	3.909	4.100, 4.300*3	4.100, 4.300*3
70	220 (8.7)	220 (8.7)	—	220 (8.7)	—	—
	267 (10.5)	267 (10.5)	241 (9.5)	241 (9.5)	267 (10.5)	267 (10.5)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
75	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	—	—	—	—	—	—
	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Standard	Standard	Standard	Standard	Standard	Standard
80	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	18.0	18.0	18.0	18.0	18.0	18.0
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				U.S.A.			
Cab Type				CrewMax			
Vehicle Grade				PLATINUM	SR5	LIMITED	PLATINUM
Model Code				USK51L-PSTZKA	USK56L-PSTSKA	USK56L-PSTLKA	USK56L-PSTZKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	—	5810 (228.7)	5810 (228.7)	—
		Width	mm (in.)	—	2030 (79.9)	2030 (79.9)	—
		Height	mm (in.)	—	1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2	—
	Wheel Base		mm (in.)	3700 (145.7)	3700 (145.7)	3700 (145.7)	3700 (145.7)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
	Effective Head Room	Front	mm (in.)	1021 (40.2)	1021 (40.2)	1021 (40.2)	1021 (40.2)
		Rear	mm (in.)	983 (38.7)	983 (38.7)	983 (38.7)	983 (38.7)
	Effective Leg Room	Front	mm (in.)	1079 (42.5)	1079 (42.5)	1079 (42.5)	1079 (42.5)
		Rear	mm (in.)	1131 (44.5)	1131 (44.5)	1131 (44.5)	1131 (44.5)
	Shoulder Room	Front	mm (in.)	1692 (66.6)	1692 (66.6)	1692 (66.6)	1692 (66.6)
		Rear	mm (in.)	1662 (65.4)	1662 (65.4)	1662 (65.4)	1662 (65.4)
	Cargo Space	Length	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Width	mm (in.)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
		Height	mm (in.)	564 (22.2)	564 (22.2)	564 (22.2)	564 (22.2)
	Overhang	Front	mm (in.)	—	890 (35.0)	890 (35.0)	—
		Rear	mm (in.)	—	1220 (48.0)	1220 (48.0)	—
	Min. Running Ground Clearance		mm (in.)	—	270 (10.6)	265 (10.4)	—
	Angle of Approach		degrees	—	29	28	—
	Angle of Departure		degrees	—	25, 20*3	25, 20*3	—
	Curb Weight	Front	kg (lb)	1390 (3065)	1488 (3280)	1504 (3315)	1508 (3325)
		Rear	kg (lb)	1132 (2495)	1125 (2480)	1150 (2535)	1150 (2535)
		Total	kg (lb)	2522 (5560)	2613 (5760)	2654 (5850)	2658 (5860)
	Gross Vehicle Weight	Front	kg (lb)	—	—	—	—
		Rear	kg (lb)	—	—	—	—
		Total	kg (lb)	3175 (7000)	3266 (7200)	3266 (7200)	3266 (7200)
	Fuel Tank Capacity		L (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
	Acceleration	0 to 60 mph	sec.	—	7.6, 7.3*3	7.6, 7.3*3	—
		0 to 400 m	sec.	—	15.9, 15.7*3	15.9, 15.7*3	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	—
		2nd Gear	km/h (mph)	—	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	—
		3rd Gear	km/h (mph)	—	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	—
		4th Gear	km/h (mph)	—	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—
		5th Gear	km/h (mph)	—	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—
		6th Gear	km/h (mph)	—	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	—	14.36 (47.1)	14.36 (47.1)	—
		Curb to Curb	m (ft.)	—	13.42 (44.0)	13.42 (44.0)	—
Engine	Engine Type			3UR-FE	3UR-FE	3UR-FE	3UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW@rpm (HP@rpm)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
	Max. Torque (SAE-NET)		N·m@rpm (ft-lbf@rpm)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 64*6	12 - 55, 12 - 64*6	12 - 55, 12 - 64*6	12 - 55, 12 - 64*6
	Generator Output		Watts	1560, 1800*3	1200, 1800*3	1560, 1800*3	1560, 1800*3
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			AB60E (6A/T)	AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)
	Gear Ratio	In 1st		3.333	3.333	3.333	3.333
		In 2nd		1.960	1.960	1.960	1.960
		In 3rd		1.353	1.353	1.353	1.353
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.728	0.728	0.728
		In 6th		0.588	0.588	0.588	0.588
		In Reverse		3.061	3.061	3.061	3.061
	Transfer Gear Ratio High/Low			—	1.000/2.640	1.000/2.640	1.000/2.640
	Differential Gear Ratio	Front		—	4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
		Rear		4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
	Differential Gear Size	Front	mm (in.)	—	220 (8.7)	220 (8.7)	220 (8.7)
		Rear	mm (in.)	267 (10.5)	267 (10.5)	267 (10.5)	267 (10.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models with P255/70R18 tire
*2: Models with P275/65R18 or P275/55R20 tire
*3: Towing package
*4: Transfer in high
*5: Transfer in low
*6: Towing package or cold area specification

U.S.A.		
CrewMax		
SR5	LIMITED	PLATINUM
USK56L-PSTSGA	USK56L-PSTLGA	USK56L-PSTZGA
5810 (228.7)	5810 (228.7)	—
2030 (79.9)	2030 (79.9)	—
1935 (76.2)*1, 1930 (76.0)*2	1930 (76.0)*2	—
3700 (145.7)	3700 (145.7)	3700 (145.7)
1725 (67.9)	1725 (67.9)	1725 (67.9)
1725 (67.9)	1725 (67.9)	1725 (67.9)
1021 (40.2)	1021 (40.2)	1021 (40.2)
983 (38.7)	983 (38.7)	983 (38.7)
1079 (42.5)	1079 (42.5)	1079 (42.5)
1131 (44.5)	1131 (44.5)	1131 (44.5)
1692 (66.6)	1692 (66.6)	1692 (66.6)
1662 (65.4)	1662 (65.4)	1662 (65.4)
1695 (66.7)	1695 (66.7)	1695 (66.7)
1687 (66.4)	1687 (66.4)	1687 (66.4)
564 (22.2)	564 (22.2)	564 (22.2)
890 (35.0)	890 (35.0)	—
1220 (48.0)	1220 (48.0)	—
270 (10.6)	265 (10.4)	—
29	28	—
25, 20*3	25, 20*3	—
1488 (3280)	1504 (3315)	1508 (3325)
1125 (2480)	1150 (2535)	1150 (2535)
2613 (5760)	2654 (5850)	2658 (5860)
—	—	—
—	—	—
3266 (7200)	3266 (7200)	3266 (7200)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
180 (111), 170 (105)*3	180 (111), 170 (105)*3	180 (111), 170 (105)*3
7.6, 7.3*3	7.6, 7.3*3	—
15.9, 15.7*3	15.9, 15.7*3	—
62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	62 (38)*4, 59 (36)*3, 4, 23 (14)*5, 22 (13)*3, 5	—
106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	106 (65)*4, 101 (62)*3, 4, 40 (24)*5, 38 (23)*3, 5	—
154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	154 (95)*4, 147 (91)*3, 4, 58 (36)*5, 56 (34)*3, 5	—
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—
180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	180 (111)*4, 170 (105)*3, 4, 68 (42)*5, 64 (39)*3, 5	—
14.36 (47.1)	14.36 (47.1)	—
13.42 (44.0)	13.42 (44.0)	—
3UR-FBE	3UR-FBE	3UR-FBE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)
94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
5663 (345.6)	5663 (345.6)	5663 (345.6)
10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI
87 or higher	87 or higher	87 or higher
284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
12 - 55, 12 - 64*6	12 - 55, 12 - 64*6	12 - 55, 12 - 64*6
1200, 1800*3	1560, 1800*3	1560, 1800*3
2.0	2.0	2.0
—	—	—
AB60F (6A/T)	AB60F (6A/T)	AB60F (6A/T)
3.333	3.333	3.333
1.960	1.960	1.960
1.353	1.353	1.353
1.000	1.000	1.000
0.728	0.728	0.728
0.588	0.588	0.588
3.061	3.061	3.061
1.000/2.640	1.000/2.640	1.000/2.640
4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
4.100, 4.300*3	4.100, 4.300*3	4.100, 4.300*3
220 (8.7)	220 (8.7)	220 (8.7)
267 (10.5)	267 (10.5)	267 (10.5)
Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
—	—	—
Double-wishbone	Double-wishbone	Double-wishbone
Rigid with Leaf Springs	Rigid with Leaf Springs	Rigid with Leaf Springs
Standard	Standard	Standard
—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type