MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				General Countries			
Body Type				3-door Hatchback		5-door Hatchback	
Vehicle Grade				—			
Model Code				NCP90L-AGMRK	NCP90L-AGPRK	NCP90L-AHMRK	NCP90R-AHMRK
Major Dimension & Vehicle Weights	Overall	Length	mm (in.)	3785 (149.0)	3785 (149.0)	3785 (149.0)	3785 (149.0)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	1530 (60.2)*1	1530 (60.2)*1	1530 (60.2)*1	1530 (60.2)*1
	Wheel Base		mm (in.)	2460 (96.9)	2460 (96.9)	2460 (96.9)	2460 (96.9)
	Tread	Front	mm (in.)	1480 (58.3)*3, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3
		Rear	mm (in.)	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3
	Room	Length	mm (in.)	1865 (73.4)	1865 (73.4)	1865 (73.4)	1865 (73.4)
		Width	mm (in.)	1390 (54.7)	1390 (54.7)	1390 (54.7)	1390 (54.7)
		Height	mm (in.)	1250 (49.2)	1250 (49.2)	1250 (49.2)	1250 (49.2)
	Overhang	Front	mm (in.)	755 (29.7)	755 (29.7)	755 (29.7)	755 (29.7)
		Rear	mm (in.)	570 (22.4)	570 (22.4)	570 (22.4)	570 (22.4)
	Min. Running Ground Clearance		mm (in.)	140 (5.5)	140 (5.5)	140 (5.5)	140 (5.5)
	Angle of Approach		degrees	19.0	19.0	19.0	19.0
	Angle of Departure		degrees	37.0	37.0	37.0	37.0
	Curb Weight	Front	kg (lb)	605 - 625 (1334 - 1378)	605 - 635 (1334 - 1400)	605 - 625 (1334 - 1378)	605 - 625 (1334 - 1378)
		Rear	kg (lb)	400 - 420 (882 - 926)	400 - 420 (882 - 926)	400 - 420 (882 - 926)	400 - 420 (882 - 926)
		Total	kg (lb)	1005 - 1045 (2216 - 2304)	1005 - 1055 (2216 - 2326)	1005 - 1045 (2216 - 2304)	1005 - 1045 (2216 - 2304)
	Gross Vehicle Weight	Front	kg (lb)	735 (1620)	745 (1642)	735 (1620)	735 (1620)
		Rear	kg (lb)	720 (1587)	720 (1587)	720 (1587)	720 (1587)
		Total	kg (lb)	1455 (3208)	1465 (3230)	1455 (3208)	1455 (3208)
	Fuel Tank Capacity		ℓ (Imp. gal.)	42 (9.2)	42 (9.2)	42 (9.2)	42 (9.2)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.272 (9.6)	0.272 (9.6)	0.272 (9.6)	0.272 (9.6)
Performance	Max. Speed		km/h (mph)	170 (105)	160 (99)	170 (105)	170 (105)
	Max. Cruising Speed		km/h (mph)	155 (96)	145 (90)	155 (96)	155 (96)
	Acceleration	0 to 100 km/h	sec.	12.4	13.7	12.4	12.4
		0 to 400 m	sec.	18.5	18.9	18.5	18.5
	Max. Permissible Speed	1st Gear	km/h (mph)	49 (30), 44 (27)*4	54 (33)	49 (30), 44 (27)*4	49 (30), 44 (27)*4
		2nd Gear	km/h (mph)	90 (56), 83 (51)*4	99 (61)	90 (56), 83 (51)*4	90 (56), 83 (51)*4
		3rd Gear	km/h (mph)	131 (81), 120 (74)*4	156 (97)	131 (81), 120 (74)*4	131 (81), 120 (74)*4
		4th Gear	km/h (mph)	167 (104), 153 (95)*4	—	167 (104), 153 (95)*4	167 (104), 153 (95)*4
	Min. Turning Radius	Tire	m (ft.)	4.7 (15.4)	4.7 (15.4)	4.7 (15.4)	4.7 (15.4)
		Body	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
Engine	Engine Type			2NZ-FE	2NZ-FE	2NZ-FE	2NZ-FE
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)
	Displacement		cm^3 (cu.in.)	1298 (79.2)	1298 (79.2)	1298 (79.2)	1298 (79.2)
	Compression Ratio			10.5 : 1, 10.0 : 1*4	10.5 : 1	10.5 : 1, 10.0 : 1*4	10.5 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output		kW/rpm	63/6000, 60/6000*4	63/6000	63/6000, 60/6000*4	63/6000
	Max. Torque		N·m/rpm	121/4400, 119/4400*4	121/4400	121/4400, 119/4400*4	121/4400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 36	12 - 36	12 - 36	12 - 36
	Alternator Output		Watts	960	960	960	960
	Starter Output		kW	0.8	0.8	0.8	0.8
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transaxle Type			C54	U441E	C54	C54
	Gear Ratio	In First		3.545	2.875	3.545	3.545
		In Second		1.904	1.568	1.904	1.904
		In Third		1.310	1.000	1.310	1.310
		In Fourth		1.031	0.696	1.031	1.031
		In Fifth		0.864	—	0.864	0.864
		In Sixth		—	—	—	—
		In Reverse		3.250	2.300	3.250	3.250
	Differential Gear Ratio (Final)			3.941, 4.312*4	4.375*5	3.941, 4.312*4	3.941, 4.312*4
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Brake Booster Type and Size		in.	Single, 9	Single, 9	Single, 9	Single, 9
	Proportioning Valve Type			—, P-valve*6	—	—, P-valve*6	—
	Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
		Rear		Torsion-beam	Torsion-beam	Torsion-beam	Torsion-beam
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			14.2	14.2	14.2	14.2
	Power Steering Type			Electric Motor	Electric Motor	Electric Motor	Electric Motor

*1: Models with raised vehicle height: + 20 mm (0.8 in.)
*2: Models with raised vehicle height: – 5 mm (0.2 in.)
*3: With 185/60R15 tire
*4: Leaded gasoline
*5: Counter gear ratio included
*6: Option

	General Countries					
	5-door Hatchback		4-door Sedan			
			—			
	NCP90L-AHPRK	NCP90R-AHPRK	NCP92L-BEMRK	NCP92R-BEMRK	NCP92L-BEPRK	NCP92R-BEPRK
	3785 (149.0)	3785 (149.0)	4300 (169.3)	4300 (169.3)	4300 (169.3)	4300 (169.3)
	1695 (66.7)	1695 (66.7)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
	1530 (60.2)*1	1530 (60.2)*1	1460 (57.5)	1460 (57.5)	1460 (57.5)	1460 (57.5)
	2460 (96.9)	2460 (96.9)	2550 (100.4)	2550 (100.4)	2550 (100.4)	2550 (100.4)
	1480 (58.3)*2, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3	1480 (58.3)*2, 1470 (57.9)*2, 3
	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3	1470 (57.9), 1460 (57.5)*3
	1865 (73.4)	1865 (73.4)	1965 (77.4)	1965 (77.4)	1965 (77.4)	1965 (77.4)
	1390 (54.7)	1390 (54.7)	1390 (54.7)	1390 (54.7)	1390 (54.7)	1390 (54.7)
	1250 (49.2)	1250 (49.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	755 (29.7)	755 (29.7)	810 (31.9)	810 (31.9)	810 (31.9)	810 (31.9)
	570 (22.4)	570 (22.4)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	140 (5.5)	140 (5.5)	150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)
	19.0	19.0	12.9	12.9	12.9	12.9
	37.0	37.0	20.1	20.1	20.1	20.1
	615 - 635 (1356 - 1400)	615 - 635 (1356 - 1400)	600 - 625 (1323 - 1378)	600 - 625 (1323 - 1378)	610 - 635 (1345 - 1400)	610 - 635 (1345 - 1400)
	400 - 420 (882 - 926)	400 - 420 (882 - 926)	405 - 420 (893 - 926)	405 - 420 (893 - 926)	405 - 420 (893 - 926)	405 - 420 (893 - 926)
	1015 - 1055 (2238 - 2326)	1015 - 1055 (2238 - 2326)	1005 - 1045 (2216 - 2304)	1005 - 1045 (2216 - 2304)	1015 - 1055 (2238 - 2326)	1015 - 1055 (2238 - 2326)
	745 (1642)	745 (1642)	730 (1609)	730 (1609)	745 (1642)	745 (1642)
	720 (1587)	720 (1587)	720 (1587)	720 (1587)	705 (1554)	705 (1554)
	1465 (3230)	1465 (3230)	1450 (3197)	1450 (3197)	1450 (3197)	1450 (3197)
	42 (9.2)	42 (9.2)	42 (9.2)	42 (9.2)	42 (9.2)	42 (9.2)
	0.272 (9.6)	0.272 (9.6)	0.475 (16.8)	0.475 (16.8)	0.475 (16.8)	0.475 (16.8)
	160 (99)	160 (99)	170 (105)	170 (105)	160 (99)	160 (99)
	145 (90)	145 (90)	155 (96)	155 (96)	145 (90)	145 (90)
	13.7	13.7	12.4	12.4	13.7	13.7
	18.9	18.9	18.5	18.5	18.9	18.9
	54 (33)	54 (33)	49 (30), 44 (27)*4	49 (30), 44 (27)*4	54 (33)	54 (33)
	99 (61)	99 (61)	96 (60), 83 (51)*4	96 (60), 83 (51)*4	99 (61)	99 (61)
	156 (97)	156 (97)	131 (81), 120 (74)*4	131 (81), 120 (74)*4	156 (97)	156 (97)
	—	—	167 (104), 153 (95)*4	167 (104), 153 (95)*4	—	—
	4.7 (15.4)	4.7 (15.4)	4.9 (16.1)	4.9 (16.1)	4.9 (16.1)	4.9 (16.1)
	5.0 (16.4)	5.0 (16.4)	5.2 (17.1)	5.2 (17.1)	5.2 (17.1)	5.2 (17.1)
	2NZ-FE	2NZ-FE	2NZ-FE	2NZ-FE	2NZ-FE	2NZ-FE
	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)	75.0 × 73.5 (2.95 × 2.89)
	1298 (79.2)	1298 (79.2)	1298 (79.2)	1298 (79.2)	1298 (79.2)	1298 (79.2)
	10.5 : 1	10.5 : 1	10.5 : 1, 10.0 : 1*4	10.5 : 1, 10.0 : 1*4	10.5 : 1, 10.0 : 1*4	10.5 : 1, 10.0 : 1*4
	EFI	EFI	EFI	EFI	EFI	EFI
	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
	63/6000	63/6000	63/6000, 60/6000*4	63/6000, 60/6000*4	63/6000, 60/6000*4	63/6000, 60/6000*4
	121/4400	121/4400	121/4400, 119/4400*4	121/4400, 119/4400*4	121/4400, 119/4400*4	121/4400, 119/4400*4
	12 - 36	12 - 36	12 - 36	12 - 36	12 - 36	12 - 36
	960	960	960	960	960	960
	0.8	0.8	0.8	0.8	0.8	0.8
	—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	—
	U441E	U441E	C54	C54	U441E	U441E
	2.875	2.875	3.545	3.545	2.875	2.875
	1.568	1.568	1.904	1.904	1.568	1.568
	1.000	1.000	1.310	1.310	1.000	1.000
	0.696	0.696	1.031	1.031	0.696	0.696
	—	—	0.864	0.864	—	—
	—	—	—	—	—	—
	2.300	2.300	3.250	3.250	2.300	2.300
	4.375*5	4.375*5	3.941, 4.312*4	3.941, 4.312*4	4.375*5	4.375*5
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Single, 9	Single, 9	Single, 9	Single, 9	Single, 9	Single, 9
	—	—	P-valve, —*6	—	P-valve, —*6	—
	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
	Torsion-beam	Torsion-beam	Torsion-beam	Torsion-beam	Torsion-beam	Torsion-beam
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	14.2	14.2	14.2	14.2	14.2	14.2
	Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor

AP

Item \ Area				General Countries			
Body Type				3-door Hatchback		5-door Hatchback	
Vehicle Grade				—			
Model Code				NCP91L-AGMRK	NCP91L-AGPRK	NCP91L-AHMRK	NCP91L-AHPRK
Major Dimension & Vehicle Weights	Overall	Length	mm (in.)	3785 (149.0)	3785 (149.0)	3785 (149.0)	3785 (149.0)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)
	Wheel Base		mm (in.)	2460 (96.9)	2460 (96.9)	2460 (96.9)	2460 (96.9)
	Tread	Front	mm (in.)	1480 (58.3)*1, 1470 (57.9)*1, 2	1480 (58.3)*1, 1470 (57.9)*1, 2	1480 (58.3)*1, 1470 (57.9)*1, 2	1480 (58.3)*1, 1470 (57.9)*1, 2
		Rear	mm (in.)	1470 (57.9), 1460 (57.5)*2	1470 (57.9), 1460 (57.5)*2	1470 (57.9), 1460 (57.5)*2	1470 (57.9), 1460 (57.5)*2
	Room	Length	mm (in.)	1865 (73.4)	1865 (73.4)	1865 (73.4)	1865 (73.4)
		Width	mm (in.)	1390 (54.7)	1390 (54.7)	1390 (54.7)	1390 (54.7)
		Height	mm (in.)	1250 (49.2)	1250 (49.2)	1250 (49.2)	1250 (49.2)
	Overhang	Front	mm (in.)	755 (29.7)	755 (29.7)	755 (29.7)	755 (29.7)
		Rear	mm (in.)	570 (22.4)	570 (22.4)	570 (22.4)	570 (22.4)
	Min. Running Ground Clearance		mm (in.)	140 (5.5)	140 (5.5)	140 (5.5)	140 (5.5)
	Angle of Approach		degrees	19.0	19.0	19.0	19.0
	Angle of Departure		degrees	37.0	37.0	37.0	37.0
	Curb Weight	Front	kg (lb)	610 - 635 (1345 - 1400)	625 - 650 (1378 - 1433)	610 - 635 (1345 - 1400)	625 - 650 (1378 - 1433)
		Rear	kg (lb)	400 - 420 (882 - 926)	400 - 420 (882 - 926)	400 - 420 (882 - 926)	400 - 420 (882 - 926)
		Total	kg (lb)	1010 - 1055 (2227 - 2326)	1025 - 1070 (2260 - 2359)	1010 - 1055 (2227 - 2326)	1025 - 1070 (2260 - 2359)
	Gross Vehicle Weight	Front	kg (lb)	745 (1642)	760 (1676)	745 (1642)	760 (1676)
		Rear	kg (lb)	720 (1587)	720 (1587)	720 (1587)	720 (1587)
		Total	kg (lb)	1465 (3230)	1480 (3263)	1465 (3230)	1480 (3263)
	Fuel Tank Capacity		ℓ (Imp. gal.)	42 (9.2)	42 (9.2)	42 (9.2)	42 (9.2)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.272 (9.6)	0.272 (9.6)	0.272 (9.6)	0.272 (9.6)
Performance	Max. Speed		km/h (mph)	180 (112)	165 (103)	180 (112)	165 (103)
	Max. Cruising Speed		km/h (mph)	165 (102)	150 (93)	165 (102)	150 (93)
	Acceleration	0 to 100 km/h	sec.	10.8	11.2	10.8	11.2
		0 to 400 m	sec.	17.8	18.3	17.8	18.3
	Max. Permissible Speed	1st Gear	km/h (mph)	51 (32)	56 (35)	51 (32)	56 (35)
		2nd Gear	km/h (mph)	96 (60)	103 (64)	96 (60)	103 (64)
		3rd Gear	km/h (mph)	139 (86)	160 (99)	139 (86)	160 (99)
		4th Gear	km/h (mph)	177 (110)	—	177 (110)	—
	Min. Turning Radius	Tire	m (ft.)	4.7 (15.4)	4.7 (15.4)	4.7 (15.4)	4.7 (15.4)
		Body	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
Engine	Engine Type			1NZ-FE	1NZ-FE	1NZ-FE	1NZ-FE
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	75.0 × 84.7 (2.95 × 3.33)	75.0 × 84.7 (2.95 × 3.33)	75.0 × 84.7 (2.95 × 3.33)	75.0 × 84.7 (2.95 × 3.33)
	Displacement		cm^3 (cu.in.)	1497 (91.3)	1497 (91.3)	1497 (91.3)	1497 (91.3)
	Compression Ratio			10.5 : 1	10.5 : 1	10.5 : 1	10.5 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output		kW/rpm	80/6000	80/6000	80/6000	80/6000
	Max. Torque		N·m/rpm	141/4200	141/4200	141/4200	141/4200
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 36	12 - 36	12 - 36	12 - 36
	Alternator Output		Watts	960	960	960	960
	Starter Output		kW	0.8	0.8	0.8	0.8
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
	Transaxle Type			C54	U340E	C54	U340E
	Gear Ratio	In First		3.545	2.847	3.545	2.847
		In Second		1.904	1.552	1.904	1.552
		In Third		1.310	1.000	1.310	1.000
		In Fourth		1.031	0.700	1.031	0.700
		In Fifth		0.864	—	0.864	—
		In Sixth		—	—	—	—
		In Reverse		3.250	2.343	3.250	2.343
	Differential Gear Ratio (Final)			3.722	4.237*3	3.722	4.237*3
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Brake Booster Type and Size		in.	Single, 9	Single, 9	Single, 9	Single, 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
		Rear		Torsion-beam	Torsion-beam	Torsion-beam	Torsion-beam
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			14.2	14.2	14.2	14.2
	Power Steering Type			Electric Motor	Electric Motor	Electric Motor	Electric Motor

*1: Models with raised vehicle height: – 5 mm (0.2 in.)
*2: With 185/60R15 tire
*3: Counter gear ratio included
*4: Option

General Countries	
4-door Sedan	
—	
NCP93L-BEMRK	NCP93L-BEPRK
4300 (169.3)	4300 (169.3)
1690 (66.5)	1690 (66.5)
1460 (57.5)	1460 (57.5)
2550 (100.4)	2550 (100.4)
1480 (58.3)*1, 1470 (57.9)*1, 2	1480 (58.3)*1, 1470 (57.9)*1, 2
1470 (57.9), 1460 (57.5)*2	1470 (57.9), 1460 (57.5)*2
1965 (77.4)	1965 (77.4)
1390 (54.7)	1390 (54.7)
1200 (47.2)	1200 (47.2)
810 (31.9)	810 (31.9)
940 (37.0)	940 (37.0)
150 (5.9)	150 (5.9)
12.7	12.7
19.9	19.9
610 - 630 (1345 - 1389)	625 - 645 (1378 -1422)
405 - 420 (893 - 926)	405 - 420 (893 - 926)
1015 - 1050 (2238 - 2315)	1030 - 1055 (2271 - 2326)
735 (1620)	755 (1709)
715 (1576)	695 (1532)
1450 (3197)	1450 (3197)
42 (9.2)	42 (9.2)
0.475 (16.8)	0.475 (16.8)
180 (112)	165 (103)
165 (102)	150 (93)
10.8	11.2
17.8	18.3
51 (32)	56 (35)
96 (60)	103 (64)
139 (86)	160 (99)
177 (110)	—
4.9 (16.1)	4.9 (16.1)
5.2 (17.1)	5.2 (17.1)
1NZ-FE	1NZ-FE
16-valve, DOHC	16-valve, DOHC
75.0 × 84.7 (2.95 × 3.33)	75.0 × 84.7 (2.95 × 3.33)
1497 (91.3)	1497 (91.3)
10.5 : 1	10.5 : 1
EFI	EFI
91 or higher	91 or higher
80/6000	80/6000
141/4200	141/4200
12 - 36	12 - 36
960	960
0.8	0.8
Dry, Single Plate, Diaphragm	—
C54	U340E
3.545	2.847
1.904	1.552
1.310	1.000
1.031	0.700
0.864	—
—	—
3.250	2.343
3.722	4.237*3
Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum
Leading-trailing Drum	Leading-trailing Drum
Single, 9	Single, 9
P-valve, —*4	P-valve, —*4
MacPherson Strut	MacPherson Strut
Torsion-beam	Torsion-beam
Standard	Standard
—	—
Rack and Pinion	Rack and Pinion
14.2	14.2
Electric Motor	Electric Motor